GEM MW

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

<b>*************</b>			····						
1. Location of well:	County	Fraction		tion number	Township number	Rang	Range number		
agged MVV Processors and a second	Inomas		1/4	# 5	т 8	S R	32	E/W	
2. Distance and direction from nearest town or city: From Colby, Ks., 3. Owner 6 miles East, ½ mile South & ½ mile East R.R. or st					Vernon Fla 1126 Terra	_	e		
Street address of well location if in city:				zip code:	Colby, Kansas 67701				
4. Locate with "X" in section below:  N					6. Bore hole dia. 28	in. Comp	oletion date 0_1 0_7	7.5	
					Well depth 250 ft.         9-19-75           7 Cable tool Rotary Driven Dug				
						B. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock			
i									
sw	LawnOil field waterOther  9. Casing: MaterialStee1 Height: Above or below Threaded Welded Surface in.								
S					RMP PVC . Dia. 16in. to 180	Wei	ght <u>. 188</u>	lbs./ft.	
5. Type and color of material				от То	Dia in. to	ft. depth gag	e No. <u>#7</u>		
Claw Canada annada					10. Screen: Manufact	urer's name	W. A. E	rown	
Clay & sand streaks				100	Type regular Dia. 16" Slot/gauze 1/8 Length 60'				
Medium to coarse sand & gravel				00 114	Set between 180 10 of cook	ft. an	212	ft.	
Clay & sand streaks			1.1	4 123	Gravel pack? <u>Yes</u>			5/8	
Medium to coarse sand & clay streaks			12	23 136	11. Static water level: mo./day/yr. $100$ ft. below land surface Date $9-20-75$				
Clay & sand stone streaks			13	36 160	12. Pumping level bel	ow land surfac	es:		
Medium to coarse sand & gravel & sand stone &					ft. after	hrs. pu	mping		
Clay streaks				50 177		Estimated maximum yield 2150 g.p.m.  13. Water sample submitted: mo./day/yr.			
					Yes1		mo	o./day/yr.	
Sand stone				77 179	14. Well head completion: Pitless adapter				
Medium to coarse sand				79 183	15. Well grouted? <u>Ves</u>				
Clay & sand stone streaks				33 186	With: Neat ceme	With: Neat cement Bentonite Concrete Depth: From ft. to ft.			
Medium to coarse sand & gravel				36 226	16. Nearest source of possible contamination:				
Medium to coarse sand & sand stone & clay streak				26 232	ft. 2600 Direction <u>East Type Farm</u> Well disinfected upon completion? Yes <u>x</u> No  17. Pump:  Manufacturer's name <u>Floway</u>				
Medium to coarse sand & gravel & clay streaks				32 238					
Medium to coarse sand & gravel				38 249	Model number	HP	<u>80                                    </u>	olts	
					Type:	<u>4.30</u> ft.	capacity	<b>∠</b> 9.p.m.	
Ochre & Shale				49 250	Submersible		<u>X</u> Turbii		
	(Use a second s	heet if needed) CT7			Centrifugal	evamente de la contraction de	Other	- 1	
18. Elevation: 19. Remarks:					20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Western Well & Pump, Inc. 245				
Topography: 3040 (TOPO)									
Hill	<i></i>				Business name	D 04.0	Li	cense No.	
Slope X Upland					Address Signed	BOX 801		houls	
Valley			W-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1		Authori	zed represent	ative Con		

Form WWC-5