VATE	R WELL	RECORD	Form WWC-	5	Division of Wate	r Resources; App. No.		
1 LOC	ATION O	F WATER WELL:	Fraction		Section Number	Township Number	Range Number	
	ty: Thoma			W 1/4	6	T 8 S	R 33 E/W	
		ection from nearest town or		ell if	Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: 39.3878			
locate	ed within ci	^{ty?} 820 S. Franklin, Colby,	, KS		Lantude.			
					Longitude: 101.0450			
2 WA	WATER WELL OWNER: E. Jay Deines□				Elevation: TOC 3166.99			
	, St. Addres	120 111 0,000			Datum:			
City,	State, ZIP	Code : WaKeeney, K	(S 67672		Data Collection	Method:		
3 LOC	ATE WEL	L'S 4 DEPTH OF COM	MPLETED WELL 155 ft.					
LOC	ATION							
WITH AN "X" IN Depth(s) Groundwater Encountered (1)							<u>, .</u> ft.	
SEC	SECTION BOX: WELL'S STATIC WATER LEVEL 141.91						_{/yr}	
N Pump test data: Well water wasft. after hours pumping.								
Est. Yield. 2.0gpm: Well water was						hours pumping gpm		
						conditioning 11 Inj	ection well	
w NV							her (Specify below)	
" -	^	2 Irrigation 4 In	ndustrial 7 Domestic	c (lawn	& garden) 10 Mor	nitoring well MW-11.		
SV	Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs							
	Sample was submitted							
S								
5 TYPE	E OF CASI	NG USED: 5 Wrough	nt Iron 8 Conc	rete tile	CASING	G JOINTS: Glued	Clamped	
			os-Cement 9 Other					
2 PVC 4 ABS 7 Fiberglass Threaded Threaded								
Casing h	neight above	land surface0.41	in., Weight.2.0		lbs./ft. Wall thi	ckness or guage No.	Sch 40	
Casing height above land surface -0.41 in., Weight 2.0 lbs./ft. Wall thickness or guage No. Sch 40 TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)								
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)								
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From. 125 ft. to 155 ft., From ft. to ft.								
From								
GRAVEL PACK INTERVALS: From. 123 ft., From ft., From ft., ft. to							ft.	
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout Intervals: From 123 ft. to 0.5 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:								
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify								
2 Sewer lines 5 Cess pool 8 Sewage-lagoon 11 Fuel storage 14 Abandoned water well below)								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well								
		LITHOLOG		FRON		PLUGGING INT		
FROM	TO 33	SILT	IC LOO	FRON	1 TO	I LUGUINO INT	LIV V ALO	
0	110	SAND						
33 110	116	CLAYEY SILT						
116	155	SAND						
110	133	SAND		<u> </u>				
		· · · · · · · · · · · · · · · · · · ·	•					
				<u> </u>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged								
under my jurisdiction and was completed on (mo/day/year) 04-30-08 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/year) 06-09-08								
		name of Woofter Pump &			y (signature)	Jay C. Wo	100	
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks inderline or circle the orrect answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone								
785-296-5		one to WATER WELL ON						

http://www.kdhe.state.ks.us/geo/waterwells.