WATER WELL RECORD	Form WWC-5	Division of Water	Resources App. No	o. L	
1 LOCATION OF WATER WELL: County: Thomas	Fraction 4 SW 4 NE 4 NW4		Township No.		
Street/Rural Address of Well Location	; if unknown, distance & direction	Global Positioning	System (GPS) in	formation:	
from nearest town or intersection: If a	Latitude: (in decimal degrees)				
Lmilt East of Colby Kunsus		Longitude: (in decimal degrees)			
2		Elevation:			
2 WATER WELL OWNER: Asriliana LLC AHn. Roy Beentin		Collection Method:			
RR#, Street Address, Box #: m530/		GPS unit (Make/Model:)			
City, State, ZIP Code : P. v. Box & 4089 ST, Aul, MN 55164-0089		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL					
SECTION BOX: Depth(s) Grou	SECTION BOX: Depth(s) Groundwater Encountered (1) N.A. ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL. NA. ft. below land surface measured on mo/day/yr. 5-21-2010				
T					
Pump test data: Well water wasft. after					
W E Bore Hole Diameter . Sin. toft., andin. toft.					
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well					
S If yes, mo/day/yr sample was submitted					
1 mile Water well disinfected? ☐ Yes No					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Glued Clamped Welded Kathreaded					
Casing diameter					
Casing height above land surface D.D					
Steel Stainless Steel SevC Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From					
From					
GRAVEL PACK INTERVALS: From 141.3 ft. to 160 ft., From ft. to ft.					
From ft. to ft., From ft. to ft. 6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Bent. 3/8 fellet 5. Grout Intervals: From G. G. D. ft. to 1.3.7.6 ft., From 1.37.6 ft. to 1.43 ft., From ft. to ft.					
Grout Intervals: From . Q. P ft. to . 1.3.7.6. ft., From . 1.37.6. ft. to . 1.43 . ft. From . ft. to . ft.					
What is the nearest source of possible con	tamination:				
Septic tank					
Sewer lines					
Direction from well		rom well			
FROM TO LITHOLO	GIC LOG FROM	TO LITHO. LO	G (cont.) or PLU	GGING INTERVALS	
N/0 / 04	1 6/5.01-				
TVU EUG / CITETIT					
WANTED BIN	nd Ocillel				
		Origi	nal Returned	to Sandar	
		for C	orrection Da	10 Seliger	
		.0.0	Oliection D	ate: <u>0/23/10</u>	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ★ constructed, □ reconstructed, or □ plugged					
under my jurisdiction and was completed on (mo/day/year)					
Kansas Water Well Contractor's License No 6.9.4 This Water Well Record was completed on (mo/day/year)					
under the business name of HW.S./. ISGATS.Ch					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212					