USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

COUBY SE

WATER WELL RECORD KSA 82a-1201-1215 Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | しりり | | | | Topeka, Kansas 66620 | | | |
|--|-------------------------------------|---------------------------|-----------------------------|----------|--|---|---|-----------------|
| 1. Kocation of well: | County | Fraction | | Section | number | Township number | Range number | |
| <u> </u> | Thomas | SE 1/4 NW 1/4 S | | #2 | 9 | т 8 s | <u> </u> | |
| / | | | vner of well: or street: | | George Epard - C/O Donna Epard RFD #1 | | | |
| Street address of well location if in city: City, | | | | | code: | Colby, Kansas | 67701 | |
| 4. Locate with "X" i | | Sketch map: | | | | 6. Bore hole dia. 28 in. Well depth 253 ft. | . Completion date 9-14-75 | |
| Ī [] | ! | | | | | 7 Cable tool Rotary | | |
| NW | NE | | | | | | Bored X_ Reverse rotary | |
| ♥ | | | | | | 8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock | | |
| x w | SE | | | | | Lawn Oi 9. Casing: Material Stee | | |
| 1 | | | | | | Threaded WeldedX_ | | |
| S . 1 Mi | | | | | | Dia. 16in. to 183 ft. dep | th Wall Thickness: inches or | |
| 5. Type and color of material | | | | From | То | Dia in. to ft. dept 10. Screen: Manufacturer's n | | |
| Clay & san | d streaks | | | 0 | 160 | Type regular | 1611 | |
| | | 1 | | 160 | | Slotygauze 10% | Length 60' | |
| Medium to coarse sand & clay streaks | | | | 160 | | Set between 183 10 of cook ft. o | ft. and 243 ft. | |
| Clay & sand stone streaks | | | | 190 | 194 | Gravel pack? <u>Ves</u> Size ra | | |
| Medium to coarse sand & gravel | | | | 194 | 220 | 11. Static water level: 153 ft. below land sur | face Date 9-18-75 | |
| Clay | | | | 220 | 223 | 12. Pumping level below land 245 ft. after 2 k | surfaces: nrs. pumping 1000 g.p.m. | |
| Medium sand | | | | 223 | 228 | ft. after hrs. pumping g.p.m. Estimated maximum yield 1000 g.p.m. 13. Water sample submitted: mo./day/yr. | | |
| Clay | | | | 228 | 232 | | | |
| Medium sand | | | | 232 | 236 | Yes X No Date 14. Well head completion: 1.0 | | |
| Clay | | | | 236 | | Pitless adapter 1 | 2 Inches above grade | |
| | | | | 1 | | 15. Well grouted? <u>Yes</u> With: Neat cement X Bentonite Concrete | | |
| Medium to coarse sand | | | | 239 | | Depth: From0 ft. to . | 10 ft. | 10 |
| Ochre & Shale | | | | 251 | 253 | 16. Nearest source of possible ft. 3900 Direction | contamination: E-SE type Farm | · |
| BROCK 751' | | | | <u> </u> | | Well disinfected upon comple | Not installed | lo |
| | | | | | | Manufacturer's nameF] | Loway | ² 0 |
| | | | | | | Model number Length of drop pipe 237 | _ HP <u>75 Volts 480</u> _ ft. capacity <u>550 g.p.</u> m. | (*) |
| | | | | | | Type: Submersible | X Turbine |) |
| | (Use a second s | heat if pended) | | | | Jet Centrifugal | Reciprocating Other | ~ V |
| 18. Elevation: | 19. Remarks: |) I needed) | | | | 20. Water well contractor's o | | ۴, |
| 2184 MIDE | | | | | | This well was drilled under my is true to the best of my know | ledge and belief. | , |
| Topography: | | | | | | Western Well & | Pump, Inc., 245 | žΚ |
| = HIII 3(4) | | | | | | Business name Address O. Box 852, Colby, Ks. | | |
| X Upland Valley | 7110 | | | | | Signed Authorized repr | nion Date Now / | ZÝ. |
| | e and pink copies to the Department | of Health and Environment | | | | | Form WWC-5 | 3 |