


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

COLBY SE

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Thomas	Fraction W 1/4 NW 1/4 NW 1/4	Section number #32	Township number T 8 S R 33	Range number EW
2. Distance and direction from nearest town or city: 4 miles South & 1 1/2 mile East Street address of well location if in city:			3. Owner of well: Richard Epard R.R. or street: 525 Austin City, state, zip code: Colby, Kansas 67701			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 36 in. Completion date 09-13-75 Well depth 265 ft.		
				7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
5. Type and color of material		From	To	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Clay & sand streaks		0	160	9. Casing: Material steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 188 lbs./ft. Dia 16 in. to 195 ft. depth Wall Thickness: inches or Dia. 16 in. to 195 ft. depth gage No. 17		
Sandy clay		160	182	10. Screen: Manufacturer's name W. A. Brown Type perforated Dia. 16" Slot/gauze 10% Length 60' Set between 195 ft. and 255 ft. 10' of cook ft. and 265 ft. Gravel pack? yes Size range of material 1/2 x 5/8		
Medium to coarse sand & gravel		182	194	11. Static water level: 150 ft. below land surface Date 9-15-75 mo./day/yr.		
Rock		194	195	12. Pumping level below land surfaces: 69 ft. after 2 hrs. pumping 1700 g.p.m. ft. after 2 hrs. pumping 1700 g.p.m. Estimated maximum yield 1700 g.p.m.		
Medium to coarse sand & gravel		195	224	13. Water sample submitted: 1700 g.p.m. mo./day/yr.		
Rock		224	226	14. Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade		
Medium sand & clay streaks		226	237	15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
Medium to coarse sand		237	252	16. Nearest source of possible contamination: ft. 2800' Direction E-SE Type Farm Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
Coarse sand		252	260	17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Floway Model number 8754 HP 100 Volts 460 Length of drop pipe 250 ft. capacity 550 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
Ochre & Shale		260	265	20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Western Well & Pump, Inc. 245 Business name License No. Address P.O. Box 852, Colby, KS. Signed Roy F. Lomax Date Nov 18 Authorized representative		
18. Elevation:		19. Remarks:		20. Water well contractor's certification:		
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley		3199 (TOPO) 3185				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5