Constal

| WATER WELL | | Form WWC-5 | | | | urces App. No. | | | |
|---|--|--|---------------------|---|----------------------|--------------------|--|-------|--|
| | WATER WELL: | | Se | ction Nu | ımber | Township Nu | imber Range Numb | | |
| | homas | 4 SE 4 SE 4 | SE 1/4 | <u>l</u> | 41 | T 8 | $\frac{S}{R}$ R $\frac{34}{R}$ DI information: | E YZW | |
| | | nown, distance & direction is address, check here □. | G10 | Dai Posi stitude: | tioning | System (Gr8) | imiormation: Gin decimal dec | rees) | |
| | | Farm Credit Office, | li | Latitude: (in decimal degrees) Longitude: (in decimal degrees) | | | | | |
| 1190 S. Range, Colby, KS 67701 | | | | Elevation: | | | | | |
| 2 WATER WELL | OWNER: JJOi | Co | | Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 | | | | | |
| RR#, St. Address, Box # : Po Box 546 | | | | Collection Method: | | | | | |
| City, State, ZIP Code : Stockton, KS 67669 | | | | ☐ GPS unit (Make/Model: ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey | | | | | |
| | | | | ☐ Digital | Map/Photo | o, U Topographic | c Map, U Land Survey | | |
| 2 LOCATE WELL | | | Lis | t. Accurac | y: LJ <31 | n, ⊔ 3-5 m, ⊔ 3 | 5-15 m, □ >15 m | | |
| 3 LOCATE WELL | i | 21238 #BST #7/P/175 \$5/#7F # | | 153 | | r. | | | |
| WITH AN "X" I | | | | | | | | | |
| SECTION BOX: | Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 141.62 ft. below land surface measured on mo/day/yr | | | | | | | | |
| N | | | | | | | | | |
| | Pun | np test data: Well water | was | II. | after | hours | pumping | gpm] | |
| NW NE - | EST. YIELD | gpm: Well water | was | II. | after | hours | s pumping | gpm | |
| w | ublic water s | rater supply Geothermal Injection well | | | | | | | |
| | ater supply | pply | | | | | | | |
| SW SE | SW SE □ Irrigation □ Industrial □ Domestic-lawn & garden ☑ Monitoring well | | | | | | | | |
| X Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☒ No <u>MW2</u> | | | | | | | | | |
| S If yes, mo/day/yr sample was submitted | | | | | | | | | |
| 1 mile Water Well Disinfected? □ Yes ☒ No | | | | | | | | | |
| 5 TYPE OF CASING USED: Steel PVC Other | | | | | | | | | |
| Steel PVC Other | | | | | | | | | |
| Casing diameter 4 in. to 120 ft., Diameter in. to ft., Diameter in. to ft. | | | | | | | | | |
| Casing neight above land surface U in., Weight 2.0/1 lbs./ft. Wall thickness or gauge No | | | | | | | | | |
| TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify) | | | | | | | | | |
| ☐ Brass ☐ Galvanized Steel ☐ None used (open hole) | | | | | | | | | |
| SCREEN OR PERFORATION OPENINGS ARE | | | | | | | | | |
| ☐ Continuous Slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) | | | | | | | | | |
| ☐ Continuous Slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify) | | | | | | | | | |
| SCREEN-PERFORATED INTERVALS: From 122 ft. to 152 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 120 ft. to 152 ft., From ft. to ft. From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft. | | | | | | | | | |
| GRAVEL PACK INTERVALS: From 120 ft. to | | | | | It., From It. to It. | | | | |
| From ft to ft !! | | | | | |)III | ft to | IL | |
| C CROUT MATER | TAT FIN (| . 50 | ^{10, 00} , | · · · · | 7.00 | | | 16. | |
| Grout Intervals E | IAL: LI Neat ceme | ent Cement grout | □ Benton | nite L | J Other | E | f) t- | | |
| Grout Intervals From 0 ft. to 116 ft. From 116 ft. to 120 ft. From ft. to ft. What is the nearest source of possible contamination: | | | | | | | | | |
| ☐ Septic tank | ☐ Lateral li | | ☐ Livestock | pens | ☐ Insect | icide storage | ☐ Other (specify be | elow) | |
| ☐ Sewer lines | ☐ Cesspool | | ☐ Fuel stora | • | | doned water wel | | , | |
| | | | | rtilizer storage Oil well/gas well Contaminated site | | | | | |
| Direction from well Distance from well | | | | | | | | | |
| FROM TO | LITHO | LOGIC LOG | FROM | TO | LITHO | . LOG (cont.) o | r PLUGGING INTER | VALS | |
| 0 .5 | Cement | | 103 | 118 | | e & clay w/sa | | | |
| .5 20 | Fill sand | | 118 | 136 | | | and w/caliche lenses | 5 | |
| 20 33 | Clay & caliche w/ | | 136 | 143 | + | ne w/sand strl | | | |
| 33 49 49 60 | Clay & caliche w/ | sang ienses clay strks & caliche len | 143 | 152 | Clay & | k caliche w/sa | na strks | | |
| 60 63 | Clay w/caliche w/ | | <u> </u> | | | | | | |
| 63 72 | | clay w/clay & caliche | | | | | | | |
| 72 85 | Fine to some med | | | | | COR | ₹FCTFI | | |
| 85 103 | | y clay w/caliche strks | | | | - COI H | \\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ | | |
| | & clay lenses | | | | | | | | |
| 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ⊠ constructed, □ reconstructed, or □ plugged | | | | | | | | | |
| under my jurisdiction and was completed on (mo/day/year) 5-12/10 and this record is true to the best of my knowledge and belief. | | | | | | | | | |
| Kansas Water Well Contractor's License No. 554 or 783 This Water Well Record was completed on (mo/day/year) 5/16/10 under the business name of Woofter Pump & Well, Inc by (signature) | | | | | | | | | |
| | | • | | | | | U00/65 | | |
| INSTRUCTIONS: Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kapsas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain | | | | | | | | | |
| one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html. | | | | | | | | | |