				R WELL RECORD F	orm WWC-5				
	ON OF WAT		Fraction	NID NO	1	ction Numbe			Range Number
County:		omas	NE 1/4	NE ½ NE  ddress of well if located	1/4	5	ј т 8	S	R 34 E(W)
Distance ar			•	le South of	•				
NATER	WELL OW		Claude		COLDY				
					- A C T.C	\+ 8	Board of	Agricultura	Division of Mater Becourse
	ddress, Box	. # .		1 Country Acres, Lot 8 Ks. 67701			Board of Agriculture, Division of Water Resources Application Number:		
City, State,		CATION WITH			20		Application		
AN "X" I	IN SECTION	OCATION WITH I BOX:	Depth(s) Ground	water Encountered 1		ft.	2	ft. 3	3
7 F	!	' X	WELL'S STATIC	WATER LEVEL . 1.1.0	ft. b	elow land s	urface measured o	on mo/day/yr	• • • • • • • • • • • • • • • • • • • •
l L.	- NW I	NE							umping gpm
	-	1 1							umping gpm
<u> </u>	i		Bore Hole Diame	ter8in. to	220	)	and	in	n. to
* w	į	. ! <b> </b> `	WELL WATER T			er supply		•	Injection well
î L	_ sw	SE	1 Domestic	_ 3 Feedlot 6	Oil field wa	ter supply	9 Dewatering	12	Other (Specify below)
	- '''	3	2 Irrigation						
l L	ı		Was a chemical/b	pacteriological sample su	bmitted to D	epartment?	YesNo	x; If yes	s, mo/day/yr sample was sub
	S		mitted			W	ater Well Disinfec	ted? Yes	No x
5 TYPE O	F BLANK C	ASING USED:		•	8 Concr			OINTS: Glue	$id {\mathbf{X}} \ldots Clamped \ldots \ldots$
1 Stee	el	3 RMP (S	R)	6 Asbestos-Cement					ded
2 PV		4 ABS		7 Fiberglass					aded
									in. to $\dots$ ft.
Casing heig	ght above la	and surface $^{1.3}$	8	in., weight 2 • .38	3 <sub></sub>	Ibs	s./ft. Wall thickness	s or gauge N	ю 2.4.8
TYPE OF S	SCREEN O	R PERFORATIO	N MATERIAL:		7 PV	'C	10 A	sbestos-cem	ent
1 Stee	el	3 Stainless	s steel	5 Fiberglass	8 RM	MP (SR) 11		Other (specify)	
2 Brass 4 Galvanized steel				6 Concrete tile 9 ABS			12 None used (open hole)		
SCREEN C	OR PERFOR	RATION OPENIN	IGS ARE:	5 Gauzed	wrapped		8 Saw cut		11 None (open hole)
1 Cor	ntinuous slo	t 3 M	lill slot	6 Wire wrapped			9 Drilled holes	3	
2 Lou	vered shutt	er 4 K	ey punched	7 Torch c					
SCREEN-P	PERFORATE	D INTERVALS:	From	1.8 0 ft. to	22.0	ft., Fr	om	ft. f	toft.
									toft.
G	RAVEL PA	CK INTERVALS:	From		22.0	ft., Fr	om	ft. 1	to
			From	ft. to		ft., Fr	om	ft.	to ft.
GROUT	MATERIAL	: 1 Neat	cement	2 Cement grout	3 Bento	onite 4	4 Other		
Grout Interv	vals: Fror	n	.ft. to 20.	ft., From	ft.	to	ft., From .		ft. toft.
What is the	nearest so	urce of possible	contamination:			10 Live	stock pens	14 A	Abandoned water well
1 Sep	otic tank	4 Later	al lines	7 Pit privy		11 Fue	l storage	15 C	Oil well/Gas well
2 Sev	wer lines	5 Cess	pool	8 Sewage lagoo	n	12 Fert	ilizer storage	16 C	Other (specify below)
3 Wa	tertight sew	er lines 6 Seep	age pit	9 Feedyard		13 Inse	ecticide storage		
Direction from	om well?	South				How m		40'	
FROM	то		LITHOLOGIC	LOG	FROM	ТО		PLUGGING I	
0	2	Surface			167	179			w/Caliche
2	20	Loess			179	191	Med. San		avel
20	55		Caliche S		191	193	Sandy Cl		
55	70			Clay Strks.	193	200	Cemented		
70	94			e Caliche					Strks.
94	100			<u>el w/Clay St</u>	200	207	Fine to	Med. Sa	and w/Clay
100	104	Sandy C	lay & Cal	iche		ļ		Str	ks.
104	135	Fine to	Med. San	d w/S. Clay	207	220	Shale		
135	136	Cemente		-					
136	145			iche Strks.					
145	147	Fine Sa	nd. Clav	& Caliche					
147	148	Caliche							
148	160			& CalicheSt					
160	163	Caliche							
163	167	Caliche	w/Clay S	trk.					
1		*			(1) constru	icted. (2) red	constructed or (3)	plugged un	der my jurisdiction and was
_					-				nowledge and belief. Kansas
				This Water Wel					
				& Well, Inc.		by (sign			voortes
				IRMLY and PRINT clearly. Pleas					
of Health	and Environm	ent, Bureau of Water	, Topeka, Kansas 6662	0-0001. Telephone: 913-296-554	5. Send one to	WATER WELL	OWNER and retain one	for your record	S.