	WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. MW6	
1 LOCATION OF WATER WELL:		7.
County: Thomas	NE " SW " NE " 18 T 8 S R 36 EN	<u>^</u>
Distance and direction from nearest tov	wn or city street address of well if located within city?	
2 WATER WELL OWNER: Brews	ster Farmers Coop	1
RR#, St. Address, Box # : 428 Ka		
City, State, ZIP Code : Brews	4 1/0 07700	'
3 LOCATE WELL'S LOCATON WITH		-
AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL 142 ft. ELEVATION:	
N	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.	OFFICE
* X	WELL'S STATIC WATER LEVEL 120, 11 ft. below land surface measured on mo/day/yr	크
	Pump test data: Well water was ft. after hours pumping gpm	- <u>M</u>
NW1XE) rn
₩ W E	Est. Yield gpm: Well water was ft. after hours pumping gpm	o
ž W	Bore Hole Diameter 8 in. to 142 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	NEA NEA
	1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
SW	2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well	
.	Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was	-
S	submitted Water Well Disinfected? Yes No X	
5 TYPE OF BLANK CASING USED:		-
		-
	(SR) 6 Asbestos-Cement 9 Other (specify below) Welded	-
(2) PVC 4 ABS	7 Fiberglass Threaded X	-
Blank casing diameter 4	in. to 110 ft., Dia in. to ft., Dia in. to ft.	
Casing height above land surface	0 in., weight 2.07 lbs./ft. Wall thickness or gauge No237 ON MATERIAL: 7 PVC 10 Asbestos-cement	_
TYPE OF SCREEN OR PERFORATION	ON MATERIAL: (7) PVC 10 Asbestos-cement	
1 Steel 3 Stainl	less steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	.l _
2 Brass 4 Galva	less steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) anized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENIN	NGS ARE: 5 (Gauzed wrapped 1.8 ISaw cut 11 None (open hole)	
	Mill slot 6 Wire wrapped 9 Drilled holes	-
2 Louvered shutter 4		-
SCREEN-PERFORATED INTERVALS	***************************************	
	From ft. to ft. From ft. to ft	20
GRAVEL PACK INTERVALS:	***************************************	
	From ft. to ft. From ft. to ft.	_
6 GROUT MATERIAL: 1 Neat	cement (2)Cement grout (3)Bentonite 4 Other	-
Grout intervals From 0	ft. to 106 ft. From 106 ft. to 108 ft. From ft. to ft.	
What is the nearest source of possible		-
1 Septic tank	4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well	
2 Sewer lines	5 Cess pool 8 Sewage lagoon 12 Fertilizer storage (16) Other (specify below)	1
Watertight sewer lines	6 Seepage pit 9 Feedyard 13 Insecticide storage Contaminated site	
Direction from well?	How many feet?	-
FROM TO CODE	LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
	urface].
	rown Clay	7 8
	rown clay w/caliche strks	╝.
	ine & Med sand w/some gravel	
	rown clay w/sand strks	_
	ine & Med sand w/clay strks	_
	emented sand	
	ine & Med sand w/some gravel	_
	clay strks	
121 143 0	lay w/sand strks	-
		\dashv
		\dashv
		\dashv
7 CONTRACTOR'S OR LANDOWALE	ER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was	\dashv
	11/14/05 and this record is true to the best of my knowledge and belief. Kansas	
Water Well Contractor's License No.		
	Woofter Pump & Well Inc. by (signature) aks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W	-
	sas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.	