1 LOCATION OF WATER WELL:	Fraction Follow	Section Number   Township Number   Range Number
County: Thomas	SE " SW" NE	7 18 T 38 S R 36 E
Distance and direction from pearest to	own or city street address of well if located within	1/2   T 1/3 S   R SL D EW
Distance and direction from nearest town or city street address of well if located within city?		
2 WATER WELL OWNER: Brewster Farmers Coop		
RR#, St. Address, Box # : 428 F		Board of Agriculture, Division of Water Resources
City, State, ZIP Code : Brew	ster, KS 6//32	Application Number:
AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	140 ft. ELEVATION:
N N	Depth(s) Croundwater Engagetered 1	(\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
A X [ ; ; ; ; ]		
		ft. below land surface measured on mo/day/yr
NWNE		s ft. after hours pumping gpm s ft. after hours pumping gpm s
	Est. Yield gpm: Well water wa	s ft. after hours pumping gpm
₹ W	E Bore Hole Diameter 8 in. to	140 ft. and in. to ft. c water supply 8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below)
	WELL WATER TO BE USED AS: 5 Public	c water supply 8 Air conditioning 11 Injection well
swse	1 Domestic 3 Feed lot 6 Office	id water supply 9 Dewatering 12 Other (Specify below)
		and garden (domestic) (10) Monitoring well
V ————————————————————————————————————	1	nitted to Department? Yes No X If yes, mo/day/yr sample was
S	submitted	Water Well Disinfected? Yes No X
5 TYPE OF BLANK CASING USED	· ·	8 Concrete tile CASING JOINTS: Glued Clamped
	P (SR) 6 Asbestos-Cement 9	9 Other (specify below) Welded
(2) PVC 4 ABS		Threaded X
Blank casing diameter 4	in. to 110 ft., Dia	in. to ft., Dia in. to ft.  107 Ibs./ft. Wall thickness or gauge No.  10 Asbestos-cement  11 Asbestos-cement
Casing height above land surface	0 in weight 2.0	17 ths /ft Wall thickness or gauge No237
TYPE OF SCREEN OR PERFORATI	ON MATERIAL:	(7) PVC 10 Asbestos-cement
1 Steel 3 Stair	nless steel 5 Fiberglass	8 RMP (SR) 11 Other (specify)
2 Brass 4 Gah	ON MATERIAL: nless steel 5 Fiberglass vanized steel 6 Concrete tile	9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPEN	IINGS ARE: 5 Gauzed v	wrapped 8 Saw cut 11 None (open hole)
	3 Mill slot 6 Wire wrap	pped 9 Drilled holes
	Key punched 7 Torch cut	(
SCREEN-PERFORATED INTERVAL	S: From <b>110</b> ft. to	140 ft. From ft. to ft.
		ft From ft to ft
GRAVEL PACK INTERVALS		140 ft. From ft. to ft.
	From ft. to	
6 GROUT MATERIAL 1 Nes	at cement 2 Cement grout	
Grout Intervals From 0 ft. to 106 ft. From 106 ft. to 108 ft. From ft. to ft.  What is the nearest source of possible contamination:  10 Livestock pens 14 Abandoned water well		
1 Septic tank		10 Livestock pens 14 Abandoned water well
2 Sewer lines		
3 Watertight sewer lines		
Direction from well?	6 Seepage pit 9 Feedyard	
FROM TO CODE	LITHOLOGIC LOG	How many feet? FROM TO PLUGGING INTERVALS
	Cement	PROM TO PLOGGING INTERVALS
	Brown Clay	
45 56 E	Brown Clay w/caliche strks	
56 69 F	ine & Med sand w/some gravel	
	clay strks	
	clay & Caliche w/some sand	
	trks	
75 109 F	ine & Med sand w/clay strks	
109 113 0	emented sand	
	ine & Med sand w/clay &	
	aliche strks	
126 143 C	lay caliche w/sand strks	
		constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was
completed on (mo/day/yr) 11/14/05 and this record is true to the best of my knowledge and belief. Kansas		
Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 11/21/05		
under the business name of Woofter Pump & Well Inc. by (signature)		
INSTRUCTIONS: Please fill in bla	nks and circle the correct answers. Send three copie	es to Kansas Department of Health and Environment/Bureau of Water, 1000 S W