

Corrected

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

[]

Well ID

MW-203

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Thomas Fraction NE 1/4 NE 1/4 SE 1/4 NE 1/4 Section Number 18 Township Number T 8 S Range Number R 36 E W

2 WELL OWNER: Last Name: Business: ADM Address: PO Box 1470 4666 Faries Parkway Decatur State: IL ZIP: 62526 Street or Rural Address where well is located: intersection of 3rd St & Oklahoma St--go south to end of Oklahoma St

3 LOCATE WELL WITH 'X' IN SECTION BOX: NW NE SW SE S

4 DEPTH OF COMPLETED WELL: 140 ft. Depth(s) Groundwater Encountered: 1) 122 ft. 2) ... ft. 3) ... ft., or 4) Dry Well WELL'S STATIC WATER LEVEL: 122 ft. below land surface, measured on (mo-day-yr) 02/16/2015

5 Latitude: 39.3628 Longitude: 101.3733 Datum: WGS 84 Source for Latitude/Longitude: GPS (unit make/model) Land Survey Topographic Map Online Mapper: 6 Elevation: 3418 ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other KOLAR

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 5. Public Water Supply: well ID 6. Dewatering: how many wells? 7. Aquifer Recharge: well ID 8. Monitoring: well ID MW-203 9. Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection 10. Oil Field Water Supply: lease 11. Test Hole: well ID Cased Uncased Geotechnical 12. Geothermal: how many bores? a) Closed Loop Horizontal Vertical b) Open Loop Surface Discharge Inj. of Water 13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 4 in. to 100 ft., Diameter 2.071 in. to 2.37 ft. Casing height above land surface 0 in. Weight 2.071 lbs./ft. Wall thickness or gauge No. 237

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 100 ft. to 140 ft., From 98 ft. to 146 ft., GRAVEL PACK INTERVALS: From 98 ft. to 146 ft.,

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 0 ft. to 5 ft., From 5 ft. to 98 ft.,

Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? Distance from well? ft.

Table with columns: 10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-2 surface, 2-25 loess, 25-42 clay w/traces of caliche & sand, 42-57 clay & caliche w/sand strks, 57-74 fine & med sand w/clay & caliche, 74-93 clay 7 caliche w/sand strks, 93-117 fine to some med sand w/clay & caliche st, 117-142 clay & caliche w/sand strks

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 02/16/2015 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 881 This Water Well Record was completed on (mo-day-year) 02/25/2015 under the business name of Wooter Pump and Well, Inc.