USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY. GUCBUNIL NE

WATER WELL RECORD KSA 82a-1201-1215

BCE

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

- *		
County Fraction	Section number	Township number Range number
1. Location of well: SHCRMAN WE W 41/4NW 1/4	5	T 8 S R 38 M
2. Distance and direction from nearest town or city: 3 N GE 15 3. Owner of well: 9ARY LOVELACE		
Street address of well location if in city: GOODIAND, KAIVS. R.R. or street: City, state, zip code: GOOD IAND, KANSAS 67735		
4. Locate with "X" in section below: N Sketch map:		6. Bore hole dia. 10 1/4 in. Completion date 2-19-17 Well depth 213 ft.
House X		7 Cable tool X Rotary Driven Dug
		Hollow rod Jetted Bored Reverse rotary
W SWSE BUNGING BAR	1	8. Use: X Domestic Public supply Industry Irrigation Air conditioning Stock
Tour Santi	V I	Lawn Oil field water Other
15 Tee / Bulding		9. Casing: Material Height: Above or below
		Threaded X Welded Surface 1 in. RMP PVC Weight 1 lbs./ft.
I < 1 Mile		Dia 42 in. to 253 ft, depth Wall Thickness; inches or
5. Type and color of material	From To	Dia. 45in. to 223 ft. depth gage No. 188 10. Screen: Manufacturer's name POBCR.
Sandstone (lay & Gravel	0 181	
	+	Type 11:11 50/7 Dia. 43 Slot/gauze 1/12 To 1/8 Length 20
Gravel	181 186	Set between 253 ft. and 273 ft.
(Lay & Sandstone	186 196	ft. and ft. Gravel pack? Size range of material
Gravel	196 200	11, Static water level: mo./day/yr,
j, aiv oc	170 200	35 ft. below land surface Date 2 16-71
Sandyclay & Sandstone	200 213	12. Pumping level below land surfaces: 12. Pumping level below land surfaces: 13. Pumping 10. g.p.m.
Gravel	213 221	ft. after hrs. pumping g.p.m.
Sandstone & Clay	221 250	Estimated maximum yield
		Yes No Date
Gravel	250 <u>268</u>	14. Well head completion:
Soapestone	268 273	Pitless adapter Inches above grade 15. Well grouted?
Shale	273	With: Neat_cement Bentonite Concrete
the second of th	+	Depth: From 6 ft. to 16 ft.
		16. Nearest source of possible contamination: ft Type
		Well disinfected upon completion? Yes No
		17. Pump: Not installed Nanufacturer's name 2.04/P.
		Model number HP Volts 230
		Length of drop pipe 200 ft. capacity 10 g.p.m.
		Type: Submersible Turbine
(1)		Jet Reciprocating
(Use a second sheet if needed) 18. Elevation: 19. Remarks: (//)	<u> </u>	Centrifugal Other Š
18. Elevation: 19. Remarks: 21 ell Was Complete Topography: + Contrete Was run Hill X Slope Upland Bef Fourt Supply Co Com. 2551 (TUDO)		This well was drilled under my jurisdiction and this report
Topography: + 1: 110to 21/as run		is true to the best of my knowledge and belief.
THIN I I have to fine.		Business name License No.
Slope Del Fous Sugar (1)		Address Schol Philadeline 249 17
<u></u>		Signed Authorized representative