

USE TYPEWRITER OR BALL POINT PEN—PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

ABB

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health  
(Water Well Contractors)  
Forbes-Bldg. 740  
Topeka, Kansas 66620

1 Location of well:	County <b>Sherman</b>	Township name <b>Washington</b>	Fraction <b>NE<sup>1</sup>/<sub>4</sub> NW<sup>1</sup>/<sub>4</sub> NE<sup>1</sup>/<sub>4</sub></b>	Section number <b>31</b>	Town number <b>8 S</b>	Range number <b>38 W</b>
---------------------	--------------------------	------------------------------------	--	-----------------------------	---------------------------	-----------------------------

Distance and direction from nearest town or city: **4S of Goodland**

Street address of well location if in city:

3 Owner of well: **Lawrence House**  
Address: **Goodland, Kansas 67735**  
**Route #2 Box 100**

Locate with "X" in section below:

N

Sketch map:

**NE<sup>1</sup>/<sub>4</sub> NW<sup>1</sup>/<sub>4</sub> NE<sup>1</sup>/<sub>4</sub> 31**  
**Sect 31, T 8 S R 38 W**

4 Well depth: 280 ft. Date of completion 2-75  
Well diameter 30 in. 2-20-75

5  Cable tool  Rotary  Driven  Dug  
 Hollow rod  Jetted  Bored  Reverse rotary

6 Use:  Domestic  Public supply  Industry  
 Irrigation  Air conditioning  Commercial  
 Test well  \_\_\_\_\_

7 Casing: Material steel Height: above/below  
Threaded  Welded  Surface 12 in.  
Dia. 16 in. Weight 36 lbs./ft.  
16 in. to 280 ft. depth Drive shoe?  Yes  No  
\_\_\_\_\_ in. to \_\_\_\_\_ ft. depth!

2	Type and color of material	From	To
	sand, sandy clay and clay	0	52
	sand	52	80
	sandy clay	80	119
	sand, good clean loose	119	148
	sandy clay	148	161
	medium to good sand	161	169
	sandy clay	169	180
	rock	180	181
	medium to good sand	181	211
	sand, clay and sandstone	211	234
	fine to medium sand	234	240
	gravel, sand clean loose	240	248
	<del>fine</del> medium sand	248	256
	sandy clay	256	269
	good sand	269	276
	shale	276	280

8 Screen: none  
Manufacturer Sargent Irrigation  
Type steel Dia. 16  
Slot gauze 2 Length 60  
Set between 220 ft. and 280 ft.  
Fittings:  
Gravel pack  Yes  No Size range of material \_\_\_\_\_

9 Static water level:  
114 ft. below land surface Date 2-75 2-21-75

10 Pumping level below land surfaces:  
127 ft. after 70 hrs. pumping 800 g.p.m.  
\_\_\_\_\_ ft. after \_\_\_\_\_ hrs. pumping \_\_\_\_\_ g.p.m.  
Estimated maximum yield 1000 g.p.m.

11 Water sample submitted:  
 Yes  No Date \_\_\_\_\_

12 Well head completion:  
 Pitless adapter  Inches above grade 12"

13 Well grouted?  Yes  No  
 Neat cement  Bentonite  \_\_\_\_\_  
Depth: From 0 ft. to 1 ft.

14 Nearest source of possible contamination: none  
ft. \_\_\_\_\_ Direction \_\_\_\_\_ Type \_\_\_\_\_  
Well disinfected upon completion?  Yes  No

15 Pump:  Not installed  
Manufacturer's name BJ Byron Jackson  
Model number Turbine HP 82 Volts \_\_\_\_\_  
Length of drop pipe 270 ft. capacity 800 g.p.m.  
Type:  
 Submersible  Turbine  
 Jet  Reciprocating  
 Centrifugal  Other

16 Remarks: elevation

3604 (TOPO)

Topography:  
 Hill  
 Slope  
 Upland  
 Valley

17 Water well contractor's certification:  
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
**Northwest Drilling Co. 248**  
Business name \_\_\_\_\_ License No. \_\_\_\_\_  
Address Scott City, Kansas  
Signed Ben Har Date 2-75  
Authorized representative 4-30-75