

1
LOCATION OF WATER WELL:
County:
Sherman
Fraction:
SW 1/4 SW 1/4 SW 1/4
Section Number:
17
Township Number:
T 8 S
Range Number:
R 39 E W

Distance and direction from nearest town or city street address of well if located within city?
Global Positioning System (decimal degrees, min. of 4 digits)
Latitude:
Longitude:
Elevation:
Datum:
Data Collection Method:

2
WATER WELL OWNER:
K D H E
RR#, St. Address, Box # :
1000 SW Jackson St Ste 410
City, State, ZIP Code :
Topeka, KS 66612-1367

3
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW
NE
SW
SE
X

N
E
S
W

4
DEPTH OF COMPLETED WELL 230 ft.
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
WELL'S STATIC WATER LEVEL 187.75 ft. below land surface measured on mo/day/yr
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well MW-31S
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr
Sample was submitted Water Well Disinfected? Yes No X

5
TYPE OF CASING USED:
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded X
Blank casing diameter 4 in. to 180 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 0 in., Weight 2.071 lbs./ft. Wall thickness or gauge No. 237
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 180 ft. to 230 ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 178 ft. to 230 ft. From ft. to ft.

6
GROUT MATERIAL:
1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals From 0 ft. to 178 ft. From 178 ft. to 180 ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well Contaminated site
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well
Direction from well? How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 2 Surface 114 120 Fine to med sd w/clay & caliche lenses
2 33 Loess 120 146 Fine to some med sd w/clay & cal strks
33 43 Clay w/caliche lenses 146 170 Caliche & clay w/sand strks
43 55 Clay & caliche w/traces of sand 170 190 Fine to some med sd w/clay & caliche strks
55 65 Fine to med sd w/clay & caliche strks 190 260 Fine to med sd w/clay & caliche strks
65 70 Fine to med sd w/clay strks & caliche 260 283 Fine to med sd w/clay & caliche lenses
Lenses 283 295 Yellow ochre/blackshale
70 85 Clay & sand strks
85 100 Fine to med sd w/clay lenses
100 114 Fine to med sd & small gravel

7
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-25-09 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 783 This Water Well Record was completed on (mo/day/year) 4-10-09 under the business name of Woofert pump & well Inc. by (signature)