USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

(Water well Contractors)

DAD

Kansas Department of Health and Environment-Division of Environment Topeka, Kansas 66620

| <u> </u> | | | | | | | , | | |
|--|----------|-------------------|-----|-----------------------------|---|---|---|---------------------------------------|--|
| 1. Location of well: | County | Fraction | | Section number | | Township number | Range number | | |
| 1. Location of well: | Sherman | MSE 1/4 NE 1/4 SE | 1/4 | 1 | | т 8 s | s R 39 | ½ ∕W | |
| | | | | ner of well: Gary Mosbarger | | | | | |
| 3½ West; 3½ North Street address of well location if in city: | | | | | | | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | 6. Bore hole dia. 30 in. Completion date 1-11-7 | | | | |
| N Sketch lidgs. | | | | | | Well depth 242 ft. | | | |
| i I | t t | | | | | 7 Cable tool Rotary | | | |
| | | | | | - | Hollow rod Jetted BoredXReverse rotary | | | |
| ₩ | | | | | | 8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock | | | |
| - | | | | | Lawn Oil field water Other | | | ther | |
| | | | | | | 9. Casing: Material Steel Height: Above althers. Threaded Welded X Surface 12 in. | | | |
| S | | | | | | RMPPVCWeight188_lbs./ft. | | | |
| 1 Mi | | | | | | Dia. 16 in. to 152 ft. de | | ches or | |
| 5. Type and color of | material | | | From | То | Dia in. to ft. de 10. Screen: Manufacturer's | | | |
| Clay | | | | 0 | 71 | Brown | | | |
| | | | | | | Type <u>Regular</u> Slot/gauze 10% | Dia16'' Length80' | | |
| Sand, Gravel | | | | 71 | 89 | Set between 152 ft. and 232 ft. | | | |
| C1ay | | | | 89 | 100 | 10 Cook 232 ft. Gravel pack? X Size r | | 5/8 50% #1 | |
| Sand Char | | | | 100 | 107 | 11. Static water level: | | ./day/yr. | |
| Sand, Gravel | | | | 100 | 107 | | urface Date 1–13- | -77_ | |
| Sandy Clay | 7 | | | 107 | 116 | 12. Pumping level below lar 192 ft. after 2 | nd surfaces: hrs. pumping 1 <u>404</u> | _ a.p.m. | |
| Coarse Sand, Gravel | | | | 116 | 125 | ft. afterhrs. pumpingg.p.m. Estimated maximum yield1404g.p.m. | | | |
| Clay, Sand, Cemented Streaks | | | | 125 | 151 | 13. Water sample submitted: mo./day/yr. | | | |
| Coarse Sand, Gravel Coarse Sand, Gravel, Clay Streaks | | | | 151 | 164 | Yes X No Date | | | |
| Clay, Cemented | | | | 164 174 | $\begin{array}{r} 174 \\ 180 \end{array}$ | 14. Well head completion: Pitless adapter | | | |
| Med. Coarse Sand, Gravel, Clay Streaks Clay | | | | 180 195 | 195 203 | 15. Well grouted? X | | | |
| Med. Coarse Sand, Gravel | | | | 203 | 210 | With: Near cement 11 benfore Concrete | | | |
| Clay SAnd, Gravel | | | | 210 213 | 213 216 | | | | |
| Sandstone | | | | 216 | 218 | 16. Nearest source of possible contamination: 17. 16. Nearest source of possible contamination: 18. 18. 18. 18. 18. 18. 18. 18. 18. 18. | | | |
| Med. Coarse Sand, Gravel | | | | 218 | 235 | Well disinfected upon completion? Yes A No | | | |
| Med. Coarse Sand, Gravel, Sandstone Streaks Coarse Sand, Gravel | | | | 235 238 | 238 241 | Manufacturer's name Floway | | | |
| Shale | | | | 241 | 242 | Model number 85076 Length of drop pipe 240 | | 1ts 480 -g.p.m. | |
| | | | | | | Type: 12"-10 S | | | |
| | | · | | | | Jet | Recipro | ocating | |
| | | sheet if needed) | | 1 | | Centrifugal | Other | , s | |
| 18. Elevation: 19. Remarks: | | | | | | 20. Water well contractor's This well was drilled under a | | s report | |
| [| | | | | | is true to the best of my kno | wledge and belief. | 1 5 | |
| Topography: | | | | | | Western Well of Business name | | 245 🕏 🕅 | |
| Slope | | | | | Address Box 852 Colby, KS 67701 | | | | |
| | | | | | | Signed Authorized representative Date 23 77 11 | | | |
| | | | | | | 10000 | 0 | · · · · · · · · · · · · · · · · · · · | |