USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

		HH				Top	oeka, Kansas 66620	
1 (County	County Fraction			number	Township number Range number		
1. Location of well:	ShERMAS	WE 1/4 NE 1/4 NE	= 1/4 2/		/	T & S H. STRUCKHOFF	R 40	X /W
~ 1	ection from nearest town or city:		1	ner of well				·
Street address of well location if in city:				R.R. or street: BOX 729 City, state, zip code: GoodLand Kansas 67235				
4. Locate with "X"		Sketch map:	1 (119, 3	idie, zip d	Lodde: C.	6. Bore hole dia. 9 i	NSAS 677_3	35
4. Locate with "X" in section below: N LEACH, Field						Well depth 298 ft. 9-22-76		
	X	^				7 Cable tool _XRotar		
NM NE				1		8. Use: X Domestic Public supply Industry		
* w				•		8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock		
						Lawn Oil field water Other		
sw se House si						9. Casing: Material PASSA Height: Above or belo w Threaded Welded Surface in.		
S	5	Well				RMP PVC	Weight	lbs./ft.
1 M	······································			1	F	Dia in. to 220ft. de	pth Wall Thickness: inch	ဦး ဂိ
5. Type and color of	f material			From	То	Dia in. to ft. de 10. Screen: Manufacturer's		
M GRAVO	-1			150	169	JESS 4 LOW	eth	
		,		750	167	Type <u> </u>	Dia Lenath	
M GRAVE	ch, SANDY CLA	14		169	190	Set between 270	_ft. and <u>296</u>	ft.
M GANU	•			190	196	Gravel pack? USSize r		ft.
Fine SAND, SAND, CLAY				196	208	11. Static water level:		day/yr.
CLAY, HARD SANDSTONE				208	212	12. Pumping level below la	nd surfaces:	
Fine SAND, SANDY CLAY				212	227	ft. after		g.p.m.
110				227		Estimated maximum yield — 13. Water sample submitted		g.p.m. day/yr.
						Yes X No	Date	
Fire SAND, M GRAVEL				232	244	14. Well head completion: X Pitless adapter	12 Inches above gr	ade
FINC SAND, SANDY CLAY				244	250	15. Well grouted? 4CS		
HARD ROCK				250	25/	With: Neat cement Depth: From ft. to	BentoniteXCo ft.	ncrete
Clay				251	258		le contamination: Let	ich,
Fire Sand Sand STON				258	274	Well disinfected upon comp		No
Fine SAND, SAND STONE TIME SAND, TRACE CLAY				274	290	17. Pump: Manufacturer's name Reg	Not installed TACKET	
O. has				290	298	Model number 1900 Length of drop pipe 355		230
CONKE	1. 19. A.L.	grand with the same		270	278	Туре:	II. capacity	1.h.m.
	<u> </u>	for Life			<u> </u>	Submersible Jet	Turbine	ating
	(Use a second	sheet if needed)			<u> </u>	Jet Centrifugal	Reciproc Other	uring
18. Elevation:	19. Remarks:	. (-5)				20. Water well contractor's		
	372:	5 (1016)				This well was drilled under is true/to the best of my kno		eport
Topography:		` /				SIHDrelling	Lo da. 16	6
—— Hill —— Slope						Business name Address	nd Kanas	ise No.
Upland						Rullin	la 0	
Valley	1					Authorized	presentative 9-22-7	·/