

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

CAA

1. Location of well: County SHERMAN		Fraction NE 1/4 NE 1/4 SW 1/4		Section number 14	Township number T 8	Range number S R 41	EW
2. Distance and direction from nearest town or city: 1 N 1/2 E 1/2 N 1/2 E				3. Owner of well: STEPHAN MANN			
Street address of well location if in city: OF Ruleton, KANS				R.R. or street: 818 WALNUT			
				City, state, zip code: GOODLAND, KANSAS 67135			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 2 1/2 in. Completion date 5-26-78			
				Well depth: 310 ft.			
				7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			
				8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other			
				9. Casing: Material STEEL Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 27.8 lbs./ft. Dia. 16 in. to 190 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 188			
5. Type and color of material				10. Screen: Manufacturer's name W.A. Brown			
				Type MILL SALT Dia. 16			
				Slot/gauze 1/4 Length 120'			
				Set between 190 ft. and 310 ft.			
				Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/2			
				11. Static water level: 160 ft. below land surface Date 4-22-78			
				12. Pumping level below land surfaces: 299 ft. after 16 hrs. pumping 600 g.p.m. 280 ft. after 16 hrs. pumping 760 g.p.m. Estimated maximum yield 760 g.p.m.			
				13. Water sample submitted: NONE mo./day/yr.			
				14. Well head completion: NONE inches above grade			
				15. Well grouted? <input checked="" type="checkbox"/> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 124 to 10 ft. below			
				16. Nearest source of possible contamination: NONE Type NONE			
				Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No			
				17. Pump: <input type="checkbox"/> Not installed Manufacturer's name NATIONAL PUMP Model number 8H12H HP 12 Volts 120 Length of drop pipe 300 ft. capacity 160 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other			
18. Elevation:		19. Remarks: BROCK 299'		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Foust Supply Co Inc 144 Business name License No. Box 338 Goodland Kansas Address Signed Paul E. Foust Date 6-6-78 Authorized representative			
Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley		Concrete WAS Run By Foust Supply Co Inc.					

T
R
E
S
E
C
1/4
1/4
1/4
1/4
NE
NW
SE
SW