


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 35 Township Number T 9 S Range Number R 18 EW

County: Rooks  
 Distance and direction from nearest town or city street address of well if located within city?  
102 W Washington Plainville KS

2 WATER WELL OWNER: Petroleum Management  
 RR#, St. Address, Box #: 14201 E Central  
 City, State, ZIP Code: Wichita KS 67230  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 19.29 ft. ELEVATION: 2140.92  
 Depth(s) Groundwater Encountered 1. 1.5 ft. 2. . ft. 3. . ft.  
 WELL'S STATIC WATER LEVEL: 14.24 ft. below land surface measured on mo/day/yr 11-2-95  
 Pump test data: Well water was . ft. after . hours pumping . gpm  
 Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm  
 Bore Hole Diameter: 8 1/4 in. to 20.5 ft., and . in. to . ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only  10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes . No ; If yes, mo/day/yr sample was sub-  
 mitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . Clamped .  
 2 PVC 4 ABS 8.9 6 Asbestos-Cement 9 Other (specify below) Welded .  
 Blank casing diameter 2 in. to 3 in. Dia. 3 in. to . ft. Dia. . in. to . ft. Dia. . in. to . ft.  
 Casing height above land surface . in. weight . lbs./ft. Wall thickness or gauge No. sch 40  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass  7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) .  
 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot  3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) .  
 SCREEN-PERFORATED INTERVALS: From 8.9 ft. to 18.9 ft. From . ft. to . ft.  
 GRAVEL PACK INTERVALS: From 7.5 ft. to 20.5 ft. From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement  2 Cement grout 3 Bentonite 4 Other .  
 Grout Intervals: From 0.5 ft. to 5.5 ft. From 5.5 ft. to 7.5 ft. From . ft. to . ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy  10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon  11 Fuel storage - Furnace 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? N How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Gravel			
0.5	10	Brown clayey silt			
10	15	Brown silty clay			
15	20.5	Wet, gray, silty sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  constructed,  reconstructed, or  plugged under my jurisdiction and was completed on (mo/day/year) 11-2-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 529 This Water Well Record was completed on (mo/day/yr) 11-10-96 under the business name of Geotechnology Inc by (signature) AT Redman