MATER WELL	RECORD	Form WWC-5	KSA 82a-1212

1 LOCAT	TON OF WA	ATER WELL:	Fraction		Se	ection Number	r Township Nu	Township Number Range		lumber
County:			SE 1/4		SE 1/4	27	T 9	S	R 18	₽ / W)
1			-	ddress of well if loca	ted within cit	y?				-
West N	Aill and C	ochran, Plainvil	lle, Kansas							
2 WATE	R WELL O	WNER: Galloway	Drilling Co.							
		×# : 105 S. Bro					Board of Agricu	lture Divis	ion of Water I	Resources
1	e, ZIP Code		Kansas 6720	2			Application Num		ion of vvaler i	(esources
, -				MPLETED WELL	25	A [I]			40.27	
P With	AN "X" IN S									
_				vater Encountered						
Ā		W		WATER LEVEL						
	N W	NE _	Pump	test data: Well wate	erwas	N.Aft.a	after	hours pur	nping	gpm
	INVV	NE E	st. Yield $\mathbf{N}\mathbf{A}$	gpm: Well wate	er was	ft. a	after	hours pur	nping	gpm
₩ W L		В	ore Hole Diame	ter8in. to	o	5ft.,	and	in.	to	ft.
≅ W _		1 1 - 1		O BE USED AS: 5			8 Air conditioning		njection well	
			1 Domestic	3 Feedlot 6	Oil field wat	er supply			other (Specify	below)
	~ SW	SE	2 Irrigation				10 Monitoring well			۲ (۲۰۰۰
		l J w		bacteriological samp						
<u> </u> ▼			ubmitted				ater Well Disinfecte			
- TVDE /	OF DLANK	CASING USED:		5 Wrought iron	8 Conc					7 4
<u> </u>				•						,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
1 SI		3 RMP (SR)		6 Asbestos-Cement		(specify bek			ed	
(2)P		4 ABS		7 Fiberglass					ded. 🕢	
i	•			ft., Dia						
Casing he	ight above l	and surface	<i>.</i> -3.72 i	n., weight	Sch 40	lbs./	ft. Wall thickness of	r gauge No	o	
TYPE OF	SCREEN C	R PERFORATION N	MATERIAL		(7)P\	/C	10 Asbe	stos-ceme	nt	
1 St	teel	3 Stainless st	teel :	5 Fiberglass	8 RN	/IP (SR)	11 Othe	r (specify)		
2 Bi		4 Galvanized		•	9 AE			used (ope		
		RATION OPENINGS			ed wrapped		8 Saw cut		11 None (ope	on hole)
	continuous s				wrapped		9 Drilled holes		ii None (op	sii iiole)
l		\ 1								
ŧ	ouvered shu	-		7 Torch			10 Other (specify)			
SCREEN	PERFORAT	ED INTERVALS:		15 ft. to						
				ft. to						
9	SRAVEL PA	CK INTERVALS:		13 ft. to						ft
				ft. to						
6 GROUT	MATERIAI	.: 1 Neat cer	ment 2	Cement grout	3 Bent	onite 4	Other			
Grout Inter	rvals: From	n	. to 1	Cement grout	.11 ft.	to 13 .	ft, From		. ft. to	ft
		ource of possible co		•			stock pens		andoned wate	
	tic tank	4 Lateral		7 Pit privy			l storage		well/Gas well	
	er lines	5 Cess po		8 Sewage lag	oon		ilizer storage	_	ner (specify b	elow)
				9 Feedyard	0011		cticide storage		rmer UST I	Posin S
Direction f	_	r lines 6 Seepag	le bir	9 reeuyalu			ny feet? 65	FQ	rmer USI i	oasın
		NW	LITHOLOGIC L	72	FROM	TOTT		GGING IN	TEDVATO	
FROM	10			<u></u>	FROIVI	10	FLC	OGING IN	IERVALO	
0		Clay, Dark Bro				-			·	
2	12	Clay, Light Bro								;
12	20	Clay, Very Ligh	it Brown							
20	25	Sand, Light Bro	own							•
						1				

					_	 -				
	 					1				
						1				
						<u> </u>				- 2
						l I	MW3, Tag # 001915	86, Flushn	nount	
						l l	Project Name: Plain	ville Yard		
							GeoCore # 553 , KD		2 10952	
7 00.	A OTOPIO	D LANDONAUTOO	CEDTEICATO	N: This water well w	ma (1)					
					oa U Const					
and was c	ompleted or	n (mo/day/year)					ecord is true to the			
				527 Th	is vvater We		/)	aay/yr)	2/4/9.8	······ ×
	business na			Services, Inc.		by (signa		KARU		
INSTRU Departr	UCTIONS: Use ment of Health	e typewriter or ball point p and Environment, Burea	pen. <i>PLEASE PRE</i> u of Water, Topeka,	SS FIRMLY and PRINT c Kansas 66620-0001. Tel	learly. Please fi ephone: 913-296	ll in blanks, unde 5-5545. Send one	erline or circle the correct e to WATER WELL OWN	answers. Se IER and retair	nd top three copie n one for your reco	es to Kansas ords.