WATE	K WEI	LL RECORD	Form W	WC-5	Divis	sion of Water	Resources App. No	o. L	
1 LOCATION OF WATER WELL:			Fraction		Section	Number	Township No.	Range Number	
County: ROOKS			14 NE 14 NE	14 NW 14		26		R 18 □E 🗹 W	
Street/Rural Address of Well Location; if unknown, distance & direction					Global Positioning System (GPS) information:				
from nearest town or intersection: If at owner's address, check here .						Latitude: (in decimal degrees)			
, –						Longitude:			
1 mile North of Plainville						Elevation:			
						Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: RON GEIST						Collection Method:			
RR#, Street Address, Box #: 2002 E 21ST						GPS unit (Make/Model:)			
City, State, ZIP Code : HAYS KS 67601					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
HATS RS 07001					Est. Accuracy:				
3 LOCATE WELL									
WIT	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL .75								
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1).40 ft. (2) ft. (3)								
	N WELL'S STATIC WATER LEVEL40ft. below land surface measured on mo/day/yr. 08-05-10								
Pump test data: Well water wasft. after hours pumping									
							ft. after hours pumping gpm		
w N	W N	E Bore Hole Diam	ore Hole Diameter 10						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well									
'		Domostio						Other (Specify below)	
SV	V S		☐ Industrial ☐						

	-		bacteriological sample				ies 🔃 No		
S If yes, mo/day/yr sample was submitted									
1 mile Water well disinfected? ☐ Yes ☑ No									
5 TYPE OF CASING USED: Steel PVC Other									
CASIN	G JOIN	rs: 17 Glued □ Clan	nped Welded	☐ Threader	i				
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .5									
Casing height above land surface. 18 in., Weight 160 lbs./ft., Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)									
Continuous stot Mili stot Gauze wrapped Torch cut Drilled notes None (open note) Louvered shutter Key punched Wire wrapped Saw cut Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
From									
Fromft. to									
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other									
Grout Intervals: From .20 ft. to .0 ft., From ft. to ft., From ft. ft.									
What is the nearest source of possible contamination:									
Septic tank									
	Sewer li			Fuel storag		Abandoned			
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well Distance from well									
FROM	TO	LITHOLOG	IC LUG	FROM	то	LITHO, LC	G (cont.) or PLU	GGING INTERVALS	
0	10	SURFACE CLAY							
10	20	YELLOW CLAY		ļ					
20	40	CLAY & SAND							
40	60	FINE SAND							
60	75	FINE & MED SAND							
				1					
				 					
				 					
7 CONTRACTORS OR LANDOWNERS CERTIFICATION. This is 11 57									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) .8-05-10 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 444 This Water Well Record was completed on (mo/day/year) 08-05-10									
under the business name of .ANDY ANDERSON DRILLING by (signature)									
INSTRUC	CTIONS:	Use typewriter or ball point pen.	PLEASE PRESS FIRMLY	and PRINT cle	arly. Please	fill in blanks	and check the correct	answers. Send three copies	
(white, blue	ue, pink) t	o Kansas Department of Health	and Environment, Bureau	of Water, Geole	gy Section,	1000 SW Jac	kson St., Suite 420, 7	Topeka, Kansas 66612-1367.	
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit us at http://www.kdheks.gov/waterwell/index.html .									
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy									