

1 LOCATION OF WATER WELL:		Fraction		Form WWC-5		KSA 82a-1212	
County: <u>ROOKS</u>		<u>SE 1/4 SE 1/4 SE 1/4</u>		Section Number <u>27</u>		Township Number <u>T 9 S</u>	
Range Number <u>18</u>		<u>EW</u>					
Distance and direction from nearest town or city street address of well if located within city? <u>West Mills & Cochran, Plainville, KS</u>							
2 WATER WELL OWNER: <u>Galloway Drilling</u>							
RR#, St. Address, Box # : <u>105 S. Broadway</u>							
City, State, ZIP Code : <u>Wichita, KS 67202</u>							
Board of Agriculture, Division of Water Resources							
Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL: <u>25</u> ft. ELEVATION:			
				Depth(s) Groundwater Encountered <u>1</u> ft. 2. ft. 3. ft.			
WELL'S STATIC WATER LEVEL <u>19.65</u> ft. below land surface measured on mo/day/yr				Pump test data: Well water was ft. after hours pumping gpm			
Est. Yield gpm: Well water was ft. after hours pumping gpm				Bore Hole Diameter in. to ft. and in. to ft.			
WELL WATER TO BE USED AS:				5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted				Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded							
7 Fiberglass Threaded							
Blank casing diameter in. to ft. Dia in. to ft. Dia in. to ft.							
Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No.							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement							
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)							
9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes							
7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL:							
1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 25 ft. to 2 ft. From 2 ft. to 0 ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)							
13 Insecticide storage							
Direction from well? How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
2 25 Cement Bentonite							
MWS							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-1-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 7-2-98 under the business name of Geocore Services, Inc. by (signature) Dan Kell							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.							