WATE	R WEI	L RECORD	Form WW	C-5		Resources App. No	<u>).</u>	
		OF WATER WELL:	Fraction		Section Number		Range Number	
Coun	County: Rooks NE 1/4 SW 1/4 NE 1/4 1/4				26	T 9 S	R 18 □E 🗗 W	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:								
from nearest town or intersection: If at owner's address, check here .					Latitude: (in decimal degrees)			
Broadway St, Plainville, Ks					Longitude: (in decimal degrees) Elevation:			
					Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Steve Felhoelter					Collection Method:			
RR#, Street Address, Box #: 1695 Y Road					GPS unit (Make/Model:)			
City, State, ZIP Code : Plainville, Ks 67663					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL								
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL .75					ft.		
SECT	TION BO							
	N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr3/12/14							
	Pump test data: Well water was. 29							
	EST. YIELD. 15gpm. Well water wasft. after							
W	W							
'	Demostic Descript Doil field mater graphy Demostrating Dethor (Specific below)							
SW	SW SE Domestic Feedlot On field water supply Dewatering Other (specify below)							
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No								
S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected?								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .5 in. to .75 ft., Diameter in. to ft., Diameter in. to ft.								
Casing height above land surface. 24								
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Speerly)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)								
Louvered shutter								
SCREEN-PERFORATED INTERVALS: From								
GRAVEL PACK INTERVALS: From .75 ft. to .20 ft., From ft. to ft.								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From .20 ft. to .0 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:								
Septic tank								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well								
		n well						
FROM	TO	LITHOLOG	IC LOG	FROM	TO LITHO. LO	OG (cont.) <u>or</u> PLU	IGGING INTERVALS	
0	2	Top Soil						
2	20	Gumbo clay						
20	42	Fine Sand						
42	65	Sand Rock						
65	68	Brown Shale						
68	72	Limestone						
72	75	Shale						
	-							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .4/18/14 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 0199 This Water Well Record was completed on the day/year) 5/2/14								
under th	e busine	ss name ofKarst Water	Well Drilling & Service	, Inc	. by (signature)	The same of the sa	Manyon for	
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								

http://www.kdheks.gov/waterwell/index.html