

1 LOCATION OF WATER WELL County: <u>Rooks</u>	Fraction <u>SW 1/4 SW 1/4 NE 1/4</u>	Section Number <u>26</u>	Township Number <u>T 9 S</u>	Range Number <u>R 18 E/W</u>
--	---	-----------------------------	---------------------------------	---------------------------------

Distance and direction from nearest town or city? 1/2 mile north of Plainville
Street address of well if located within city?

2 WATER WELL OWNER: Richard Werner
RR#, St. Address, Box # : R. R.# 2
City, State, ZIP Code : Plainville, Kansas 67663
Board of Agriculture, Division of Water Resources
Application Number:

3 DEPTH OF COMPLETED WELL: 50 ft. Bore Hole Diameter: 12 in. to ft., and in. to ft.
Well Water to be used as:
1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
7 Lawn and garden only 10 Observation well
Well's static water level: 30 ft. below land surface measured on January month 24 day 1981 year
Pump Test Data : Well water was 20 ft. after 2 hours pumping 13 gpm
Est. Yield 15 gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded
Blank casing dia: 6 in. to 30 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface: 24 in., weight 3.58 lbs./ft. Wall thickness or gauge No. 280

TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
9 ABS 12 None used (open hole)
Screen or Perforation Openings Are:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)
Screen-Perforation Dia: 6 in. to 50 ft., Dia in. to ft., Dia in. to ft.
Screen-Perforated Intervals: From 30 ft. to 50 ft., From ft. to ft.
Gravel Pack Intervals: From 10 ft. to 50 ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well
2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well
3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below) none
Direction from well How many feet ? Water Well Disinfected? Yes No
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample was submitted month day year: Pump Installed? Yes No
If Yes: Pump Manufacturer's name Model No.HP Volts
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on January month 24 day 1981 year
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 285
This Water Well Record was completed on February month 2 day 1981 year under the business name of Jones Brothers Water well Service by (signature) James K. Jones

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
	0	24	top soil			
	24	45	sand			
	45	48	clay			
	48	50	blue shale			
ELEVATION: level						

Depth(s) Groundwater Encountered 1. 30 ft. 2. 45 ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
9
R
18
E/W
SEC.
26
SW 1/4
SW 1/4
NE 1/4