WATEI	R WEI	L RECORD	Form W	WC-5		Resources App. No	. [	
1 LOCATION OF WATER WELL: County: Rooks		Fraction	1/4 1/4	Section Number 35		Range Number R 19		
Coun	ty: Koo	ks Address of Well Location;	SE 1/4 SE 1/4 SW					
from	nearest f	own or intersection: If at	nwner's address, check	Global Positioning System (GPS) information:  Latitude: (in decimal degrees)				
From Zurich, Ks 1 mile east 3/4 mile south.					Longitude: (in decimal degrees)			
LION.	II ZUIKI	, No I tille east of the	, 300ui.		Elevation:			
2 WATER WELL OWNER: Matt Saindoni					Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: 2340 11 RD					GPS unit (Make/Model:)			
City, State, ZIP Code : Zurich, Ks 67663					Digital Map/Photo, Topographic Map, Land Survey			
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m								
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 60 ft.								
	SECTION BOX: Depth(s) Groundwater Encountered (1).25							
	N WELL'S STATIC WATER LEVEL							
	Pump test data: Well water was .45							
EST. YIELD. 5gpm. Well water wasft. after								
w	W   Bore Hole Diameter 10 in. to .60 ft., and in. to							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well  Feedlot Oil field water supply Dewatering Other (Specify below)								
sw-Xse								
Was a chemical/bacteriological sample submitted to Department? Yes V No								
S If ves. mo/day/vr sample was submitted								
Water well disinfected? ☑ Yes ☐ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS:  Glued  Clamped  Welded  Threaded								
Casing diameter .5 in. to .60 ft., Diameter in. to ft., Diameter in. to ft.								
Casing height above land surface. 24								
TYPE OF SCREEN OR PERFORATION MATERIAL:  Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From 60 ft. to 40 ft., From ft. to ft.								
From ft. to ft. from ft. ft. ft. ft.								
GRAVEL PACK INTERVALS: From 60 ft. to 20 ft., From ft. to ft.								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From 20								
What is the nearest source of possible contamination:  Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
	Sewer li			Fuel storage			or (specify below)	
☐ Watertight sewer lines ☐ Scepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oll well/gas well								
		n well					CODIC DETENTION	
FROM	TO 29	LITHOLOG	HC LOG	FROM	TO LITHO. LO	OG (cont.) or PLU	GGING INTERVALS	
2	30	Fine Sand						
30	43	Gumbo Fine Sand						
43	44	Gumbo Clay						
44	50	Sand Rock						
50	57	Clay						
57	60	Shale						
7.00	TD A C	DICORT AMBOUR	NO CEDITION AND	N. True		-4-1 [7]		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \( \sqrt{\omega}\) constructed, \( \sqrt{\omega}\) reconstructed, or \( \sqrt{\omega}\) plugged under my jurisdiction and was completed on (mo/day/year) .09/04/12 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No0199 This Water Well Record was completed of Waterland 12								
	_ 1	Karet Water	Wall Drilling & Sand	ce inc	1 (-i		20 miles	
INSTRUC	TIONS:	Use ty pewriter or ball point pen	PLEASE PRESS FIRMLY	and PRINT cle	erly. Please fill in blanks	and check the correct	answer. Statute of the	
I (without one	ш, ришь, и	Kansas Depar tment of Health 5524. Send one copy to WAT	STATE TO TATE OF TAXABLE AND ADDRESS OF	DI 11 MICH, COOLO	<b>2) DOMENT TOOK OUT 12</b>	ADDITION, DUMP TAV.	1000MA, RABIGAS 00014-1301.	