


1 LOCATION OF WATER WELL: County: <u>ROOKS</u>	Fraction <u>SE 1/4 SW 1/4 SW 1/4</u>	Section Number <u>21</u>	Township Number T <u>9</u> S	Range Number R <u>20</u> EW <u>6</u>
---	---	-----------------------------	---------------------------------	---

Distance and direction from nearest town or city street address of well if located within city?

602 Ash, Paico, KSMW-6

2 WATER WELL OWNER: <u>USD #269</u> RR#, St. Address, Box # : <u>602 Ash</u> City, State, ZIP Code : <u>Paico, KS</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: <u>84.0</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>73</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>73.25</u> ft. below land surface measured on mo/day/yr <u>1/11/95</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> Was a chemical/bacteriological sample submitted to Department? Yes <u>NO</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>NO</u>
---	---

5 TYPE OF BLANK CASING USED: 1 Steel <u>2 PVC</u> Blank casing diameter <u>2</u> in. to <u>64.0</u> ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface <u>0</u> in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>64.0</u> ft. to <u>84.0</u> ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>63.0</u> ft. to <u>84.0</u> ft. From ft. to ft. From ft. to ft. From ft. to ft.	CASING JOINTS: Glued Clamped Welded <u>Threaded</u>
--	---

6 GROUT MATERIAL: 1 Neat cement <u>2 Cement grout</u> <u>3 Bentonite</u> 4 Other Grout Intervals: From <u>64.0</u> ft. to <u>61.0</u> ft. From <u>61.0</u> ft. to <u>63.0</u> ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy <u>10 Fuel storage</u> 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	1.5'	Asphalt			
1.5'	33.0'	Clay w/silt, brown			
33.0'	38.0'	Sand, fine grained, w/silt, light brown			
38.0'	52.0'	Clay w/silt, brown			
52.0'	60.0'	Sand, medium grained			
60.0'	72.0'	Clay w/silt & fine grained sand, light brown			
72.0'	84.0'	Sand, fine to coarse grained, w/silt & clay, light brown, wet at 73'			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>1</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1/18/95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>438</u> This Water Well Record was completed on (mo/day/yr) <u>1/18/95</u> under the business name of <u>Kansas City Testing Lab</u> by (signature) <u>Charles Harper</u>
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.