WATER WELL RECORD Form WWC-5 Division of Water Resources App. No.								
1 LOC	ATION	OF WATER WELL:	Fraction		Section Number	Township No.	Range Number	
	ty: Grah	· · · · · · · · · · · · · · · · · · ·	1/4 NE 1/4 NE			T 9 S	R 21 □E 🗹 W	
	Street/Rural Address of Well Location; if unknown, distance & direction					Global Positioning System (GPS) information:		
	from nearest town or intersection: If at owner's address, check here					Latitude: (in decimal degrees) Longitude: (in decimal degrees)		
1 1011	Trom boydo, INO Timios cast, Timios south					Elevation:		
					Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Tim Benoit					Collection Method:			
RR#, Street Address, Box #: 3986 O RD City, State, ZIP Code Damar KS 67632					☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City, State, ZIP Code : Damar, KS 67632						Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m		
3 LOCATE WELL								
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 30 ft.							
SECT	Depth(s) Groundwater Encountered (1).14 ft. (2)							
г	Pump test data: Well water wasft. after							
, , ,	EST. YIELD.4							
w [NW	W Bore Hole Diameter 10 in. to .30 ft., and in. to ft.							
<u> </u>	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SW SE Domestic								
	☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
S If yes, mo/day/yr sample was submitted								
Water well disinfected? Ves No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .5. in. to .30 ft., Diameter in. to ft., Diameter in. to ft.								
Casing height above land surface. 24. in., Weight 2.91. lbs./ft., Wall thickness or gauge No.								
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From .7								
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
	Sewer lir	es	Sewage lagoon	Fuel storag	e 🔲 Abandoneo	d water well	(opening one ii)	
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
		n wellLITHOLOG			from well		COTAC DETERMINE	
FROM 0	TO 5	Top soil	IC LOG	FROM	TO LITHO. LO	OG (cont.) or PLO	GGING INTERVALS	
5	12	sand and gravel			·)			
12	13	rock						
13	30	shale						
								
						· · · · · · · · · · · · · · · · · · ·		

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) $1.7.93.1.9$ and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 0199 This Water Well Record was completed on (mo/day/year). 0940-14								
under th	e busine	ss name ofKarst Water	Well Drilling & Serv	ice, Inc	by (signature)	Carl Beneral		
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								

http://www.kdheks.gov/waterwell/index.html.