WATER WELL RECORD		Form W	WC-5	Div	Division of Water Resources App. No.			
		Fraction		1	n Number	Township No.	Range Number	
County: GRAHAM		NE 1/4 NE 1/4 SE			23	T 9 S	R 23 □E ☑W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here .						g System (GPS) in		
from nearest town or intersection. If at owner's address, check here ψ .					Latitude:			
					Elevation:			
2 WATER WELL OWNER, AND AND TO COM					Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: ANDY ANDERSON RR#, Street Address, Box #: 1829 US HWY 283				Collection Method: GPS unit (Make/Model:)				
City, State, 2	TTD C 1	TY KS 67642 Digital Map/Photo, Topographic Map,						
	THE OF	11 K3 07042		Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m				
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 130 ft.								
SECTION BO	OX: Depth(s) Groundwater Encountered (1).90 ft. (2) ft. (3) ft.							
N	WELL'S STATIC WATER LEVEL. 90ft. below land surface measured on mo/day/yr. 08-1.5-11							
Pump test data: Well water wasft. after hours pumping gp								
					ft. after hours pumping gpm			
W Bore Hole Diameter 10 in. to								
Domestic Decellet Doil field vector cumply Developing Dether (Specify below)								
Irrigation ☐ Industrial ☑ Domestic-lawn & garden ☐ Monitoring well								
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No								
S If yes, mo/day/yr sample was submitted								
Water well districted.								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .5								
Casing diameter								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel PVC Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)								
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
GRAVEL PACK INTERVALS: From 130 ft. to 40 ft., From ft. to ft.								
From								
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ✓ Bentonite ☐ Other								
Grout Intervals: From .30 ft. to .0 ft., From								
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
	m well							
FROM TO 10	LITHOLOG SURFACE CLAY	IC LOG	FROM	TO	LITHO, L	OG (cont.) or PLU	JGGING INTERVALS	
10 50	HARD YELLOW CLAY						- 1814 M HV/181	
50 60	HARD LIMESTONE							
60 80	SANDY GRAY CLAY							
80 90	FINE SAND							
90 110	MED SAND	AND.						
110 115 115 130	HARD WHITE LIMEST MED TO LARGE SANI							
110 130	WILD TO LANGE SANI	J						
						T		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .08-15-11 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 444 This Water Well Record was completed on (mo/day/year) 08-15-11								
under the business name of .ANDY ANDERSON DRILLING by (signature)								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								