

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: SHERIDAN	SW 1/4 NW 1/4 NW 1/4	26	T 9 S	R 26 E <u>W</u>

Distance and direction from nearest town or city street address of well if located within city?
 7 miles South 1 miles West 1/2 mile South of Suttley

2 WATER WELL OWNER: ALVIN KUHN
 RR#, St. Address, Box # : 310 ELDORADO LANE Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : HAYS KS 67601 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
	Depth(s) Groundwater Encountered	115 ft.
	WELL'S STATIC WATER LEVEL	115 ft. below land surface measured on mo/day/yr 11-10-05
	Pump test data: Well water was	3.0 gpm
	Est. Yield	3.0 gpm
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well X X Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X.X.</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X X</u>		

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X X</u> Clamped
<u>X X</u> PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
	5	7 Fiberglass		Threaded

Blank casing diameter in to 105 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 10 in., weight 160 lbs./ft. Wall thickness or guage No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	<u>X X</u> RVC	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	<u>X X</u> slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 105 ft. to 145 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 8.0 ~~ft.~~ ft. to 145 ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement	2 Cement grout	<u>X</u> Bentonite	4 Other
0	25		

Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	SURFACE CLAY			
10	20	YELLOW CLAY			
20	40	MED SAND			
40	90	GRAY CLAY			
90	110	FINE SAND			
110	140	MED SAND			
140	145	FINE SAND			
145	146	X CAP ROCK			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-10-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 444 This Water Well Record was completed on (mo/day/yr) 11-10-05 under the business name of ANDY ANDERSON DRILLING by (signature) Andy Anderson