


1 LOCATION OF WATER WELL: Fraction  $\frac{1}{4}$  C  $\frac{1}{4}$  SW  $\frac{1}{4}$  Section Number 20 Township Number T 9 S Range Number R 27 EW

Distance and direction from nearest town or city street address of well if located within city?  
 6 Miles South 4 East 3/4 South 1/4 East of Hoxie, Kansas

2 WATER WELL OWNER: Max Kennedy  
 RR#, St. Address, Box #: Rt. 2  
 City, State, ZIP Code: Hoxie, Kansas  
 Board of Agriculture, Division of Water Resources  
 Application Number: 39 282

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  


4 DEPTH OF COMPLETED WELL: 217 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 140 ft. below land surface measured on mo/day/yr 4-7-89  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter 28 in. to 217 ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter 16 in. to 137 ft., Dia 16.4 in. to ft., Dia in. to ft.  
 Casing height above land surface 12 in., weight 16.4 lbs./ft. Wall thickness or gauge No. 500  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)  
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 137 ft. to 217 ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 20 ft. to 217 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? Southeast How many feet? 1300

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	127	Surface			
127	129	Fine Sand			
129	137	Clay			
137	140	Med. Sand			
140	152	Caliche, thin cemented sand Strk			
152	178	Caliche, Clay med. Sand			
178	180	Med. Sand			
180	181	Caliche			
181	197	Med. Sand, Clay			
197	199	Coarse Gravel			
199	204	Caliche & Cemented sand strks.			
204	213	Med. Sand to coarse Sand			
213	214	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-7-89 and this record is true to the best of my knowledge and belief. Kansas  
 Water Well Contractor's License No. 394 This Water Well Record was completed on (mo/day/yr) 5-29-89  
 under the business name of Woofter Pump & Well by (signature) Walt Winkler

OFFICE USE ONLY