WATER WELL RECORD KSA 82a-1201-1215 Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

		12.	<u> </u>							
	County	Fraction			Section	number	Township number	Range number		
1. Location of well:	Sheridan	SW _{1/4}	SE 1/4 S	E _{1/4}	2	1	T 9 S	_R 28	₹∕w	
Trom che The					er of well	-	Floyd Chapman			
Hoxie of 23/24 - 7½ S. 1½ N. to Well Site R.R. or Street address of well ocation if in city: 1½ W. City, sh							Box 175			
						ode:	Hoxie, KS 67740	Completion date		
4. Lacate with "X" in section below: N Sketch map:							6. Bore hole dia. <u>30</u> in. Well depth <u>205</u> ft.	8-18-7	8	
<u> </u>							7 Cable tool Rotary Driven Dug			
NW NE						Hollow rod Jetted BoredXReverse rota				
<u>*</u> ₩							8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock			
[LawnOil field waterOther			
SW SE							9. Casing: Material Kight Above below Threaded Welded in.			
<u>† ' ' X '</u> S							Threaded Welded Weight Ibs./ft.			
1 Mi							Dia. 16in. to X. 21:9dep		ches or	
5. Type and color of	material				From	То	10 Screen: Manufacturer's n	TT 4 D	own -	50¹
Top Soil					0	100		Dig. 16"		
Sandy Clay					100	123	Slot/gauze 10% Length 50 t			
Med. Coarse Sand, Small Gravel					123	130	ft. andft.			
					+		1			
Sandy Clay, Fine Sand				130	138					
Fine Med. Sand					138	144	12. Pumping level below land surfaces: 166 ft. after 2 hrs. pumping 654 g.p.m.			
Med. Coarse Sand, Small Gravel					144	156	ft. after hrs. pumping g.p.m.			
Fractured Sandstone, Med. Coarse Sand, Small Gravel					156	165	13. Water sample submitted: mo./day/yr.			
Med. Coarse Sand, (Fractured Sst. 165'-166')					165	184				
Sandy Clay					184	190	Pitless adapter 12 Inches above grade 15. Well grouted? X			
Fine Sand					190	193	3 With: Neat cement Bentonite X Concrete			
Med Coarse Sand Fractured Set Clay Longe					193	203	Depth: From ft. to ft. 16. Nearest source of possible contamination:			
Med. Coarse Sand, Fractured Sst., Clay Lense Ochre, Shale					203		ft. 2600 Direction SSE Type Farmstea			
Ochre, Share				203	220	Well disinfected upon comple	etion?Yes _ Not installed	<u>X</u> No	1-12	
5 KOCK 203'						Manufacturer's nameF	'loway		$ \mathscr{J} _{\mathbb{Z}}$	
·						Model number _10 DOH Length of drop pipe _190			(₹) ™	
						Type: Submersible	XTurbine			
						Jet	Recipro		K í	
<u> </u>	* . ********** ·	sheet if needed)			<u> </u>	Centrifugal	Other		
18. Elevation:	19. Remarks:						20. Water well contractor's of This well was drilled under m		s report	' \
							is true to the best of my know	•	•	- M
Topography: Hill						Western Well & Pump, Inc. 2/			245 ense No.	312
Slope						Address 10 852 Colby, KS 6770			67701	212
							Signed Authorized rep	Date	X/23/17	[<u>\$15</u>]
variey										- W