CAA

WATER WELL RECORD KSA 82a-1201-1215



Kansos Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | NE NE CH | | Section number 34 | | Township number | Range number | | |
|--|--------------|---|--|--|-----|--|------------------------------------|------------------------------------|--|
| 1. Location of well: | Sheridan | | | | | T 9 s | _R 28 | | |
| 2. Distance and direction from nearest town or city: Hoxie, Kansas | | | | 3. Owner of well: Tom Haffner | | | | | |
| 8½ South; ½East Street address of well location if in city: | | | | R.R. or street: | | | | | |
| | City, s | City, state, zip code: Grainfield, KS 67737 6. Bore hole dia. 30 in. Completion date | | | | | | | |
| 4. Locate with "X" in section below: N | | | | | l | Well depth 181 ft. 12-16-78 | | | |
| Ī I | | | | | Ì | 7 Cable tool Rotary Driven Dug | | | |
| = NW NE - E | | | | | ļ | 8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock | | | |
| | | | | | | | | | |
| [| | | | Lawn Oil field water Other | | | | | |
| 5\\ | | | | 9. Casing: Material Steel Height: Above or below | | | | | |
| | | | | Threoded WeldedX Surface in. RMP PVC Weight 1.75 lbs./ft. | | | | | |
| 1 Mile ——→1 | | | | 1 | | Dio.16 in. to 181 ft. dept | h Wall Thickness; inc | hes or | |
| 5. Type and color of material | | | | From | То | Dia in. to ft. dept 10. Screen: Manufacturer's n | COOK | | |
| Clay & Layers of Gravel | | | | a | 80 | | | | |
| | | | | | | Slot/gauze100 Length10 | | | |
| Sand & Gravel | | | | 80 | 90 | Set between 171 ft. and 181 ft. | | | |
| Clay Sandy | | | | 90 | 127 | Gravel pack? _X Size ran | nd | <u></u> ft. 5/8 | |
| Coarse Sand & Gravel | | | | 127 | | 11. Static water level: | mo./ | day/yr. | |
| | | | | | | LO1 ft. below land surf | | <u>-78</u> | |
| Clay | | | | 138 | 146 | $\frac{12. \text{ Pumping level below land}}{173}$ ft. after $\frac{2}{100}$ h | surfaces: rs. pumping 798 | g.p.m. | |
| Coarse Sand & Gravel | | | | 146 | 152 | ft. after h | rs. pumping | g.p.m. | |
| Clay & Sand & Gravel Layers | | | | 152 | 165 | Estimated maximum yield 13. Water sample submitted: | | g.p.m. /day/yr. | |
| | | | | | | | Date | | |
| Coarse Snad & Gravel | | | | 165 | 178 | 14. Well head completion: 12 | Inches above g | rade | |
| Ochre & Shale | | | | 178 | 185 | 15. Well grouted? X | | 1 | |
| ļ | | | | | | With: Neat cement | | oncrete - | |
| | BROCK | 108' | | | | Depth: From ft. to 16. Nearest source of possible | | - | |
| | 122001 | | | | | ft.6000 Direction N | W Type Farn | stead | |
| | | | | ļ | | Well disinfected upon completed. 17. Pump: | Not installed | X No | |
| | | | | | | Manufacturer's name F1 | .oway | | |
| | | | | | | Model number 10DOH Length of drop pipe 179 | HP60Volt ftcapacity 70 0 | ·—— i | |
| | | | | | | Type: X | | | |
| | | | | <u> </u> | | Submersible Jet | Turbine Reciproc | atina k | |
| (Use a second sheet if needed) | | | | | | Centrifugal | Other | Sec | |
| 18. Elevation: | 19. Remarks: | | | | | 20. Water well contractor's c This well was drilled under my | | eport | |
| Topography: | | | | | | is true to the best of my knowledgestern Well & | | 245 ≨ [| |
| | | | | | | Business name 852 Co | | <u>-24</u> -1 × 15 2701: - 1= | |
| Slope X Upland | | | | | | Address BOX 832 CC | ALLEY, NO 101 | //J | |
| Upland Valley | · | | | | | Signed Authorized repr | esentative ate | -/6-//- K | |