

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Thomas	W/2 1/4 NW 1/4 NW 1/4	4	T 9 S	R 31 EW

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER:	Janet Blevins	White & Ellis Drilling, Inc.
RR#, St. Address, Box # :	RR 1 Box 790	P. O. Box 1586
City, State, ZIP Code :	Edgecomb, ME 04556	Great Bend, KS 67530
		Board of Agriculture, Division of Water Resources
		Application Number: 960300

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 193 ft. ELEVATION:
	Depth(s) Groundwater Encountered 123 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 123 ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to 193 ft. and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 4.5 in. to 153 ft. Dia. in. to ft. Dia. in. to ft.			
Casing height above land surface 18 in. weight 2.38 lbs./ft. Wall thickness or gauge No. 248			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 153 ft. to 193 ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 193 ft. From ft. to ft. From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft.				
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well		
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well				
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)				
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage				
Direction from well? SE		How many feet? 150		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface	146	168	Sandy Clay w/Some Sand
2	16	Loess	168	178	Med. Sand & Gravel
16	55	Clay & Caliche	178	182	Sandy Clay
55	60	Med. Sand & Gravel w/Clay Str.	182	187	Ochre
60	74	Cemented Sand w/Sand & Clay Str.	187	193	Shale
74	84	Fine to Med. Sand w/aFew Cem. Clay Strks.			
84	85	Cemented Sand			
85	95	Sandy Clay w/Cemented Strks.			
95	104	Fine to Med. Sand			
104	115	Tight Med. Sand w/Cem. Strks.			
115	127	Med. Sand & Gravel			
127	131	Sandy Clay			
131	142	Fine to Med. Sand			
142	146	Cemented Sand w/Med. Sand Str			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-14-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 9-16-96 under the business name of Woofter Pump & Well, Inc. by (signature) [Signature]
