USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215 Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

Well #1

220000000000000000000000000000000000000	County	Fraction Se		Section number		Township number	Range number		
1. Location of well:	Thomas	SW 1/4 SW 1/4 SW	1/4	17	7	T 9 s	R 31	\$∕W	
					er of well: Leon Stoppe1				
9 East; 9 South; 3 East Street address of well location if in city: R.R. or s									
City, sta				ate, zip code: Oakley, KANAXX KS				2-23-76	
4. Locate with "X" in section below: Sketch map:					6. Bore hole dia. $\frac{30}{189}$ in. Completion date $\frac{12-23-7}{189}$ ft.				
Ī []	CONTROL OF THE STATE OF THE STA					7 Cable tool Rotary	CONTRACTOR OF THE PROPERTY OF)	
NW	NE					Hollow rod Jetted			
' <u>□</u> W						8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock			
						LawnOil field waterOther			
						9. Casing: Materia Steel Height: Above or Welded X Surface XX 12 in.			
<u>† </u>						Threaded Welded _X Surface X 12 in. RMP PVC Weight . 188 lbs./ft.			
_	-		umma ka	uquinani una ana ana	-	Dia.16 in. to 119 ft. dep	ith Wall Thickness: ir	nches or	
5. Type and color of material				From	То	Diain. toft. depth gage No#/			
0 1 01					1/0	Brown			
Coarse Sand, Clay				0	140	Type Regular Dia. 16" Slot/gauze XXX 10% Length 60'			
Coa. Sand, Med. Gravel, KXXX Clay Streaks				140	160	Set between 119 ft. and 179 ft.			
Coa. Sand, Clya, Sandstone Streaks, Med. Gravel				160	180	10 Cook 179 ft. and 189 ft. Gravel pack? X Size range of material 30%#1 70 74x			
Coa. Sand, Med. Gravel, Clay Streaks				180	180	11. Static water level: mo./day/yr.			
doa. band, ned. draver, dray briedes				100	100	ft. below land sur		7-76	
Ochre, Shale				189		12 . Pumping level below land 186 ft. after 2 .	d surfaces: hrs. pumping 1360	<u>)</u> g.p.m.	
15 ROCK 189°						ft. after hrs. pumping g.p.m.			
		Į.				13. Water sample submitted:		g.p.m.	
					·	Date			
)						14. Well head completion: Pitless adapter 12 Inches above grade			
					ļ	15. Well grouted? X Clay With: Neat_cement X Bentonite X Concrete			
				-	ļ	Depth: From 0 ft. to 10 ft.			
						16. Nearest source of possible ft. 2 M Direction 1	e contamination;	use T	
						Well disinfected upon comple	etion? Yes	X No	
	ente ente folde de l'est au control de des décidents de l'entre en entre entre entre en entre entre entre entre	T PATA PERMITTEN PERMITINAN DEPENDENTAL AND OPEN DE MARCO GOVERNO CONTRACTOR DE CONTRACTOR DE CONTRACTOR DE C				17. Pump:	Not installed 1oway		
			······································			Model number 85053	00	olts	
			***************************************		ļ	Length of drop pipe 175	ft. capacity	g.p.m. \	
						Type: Submersible	X Turbin	ne .	
	//			<u> </u>		Jet	Recipr	rocating	
18. Elevation:	(Use a second s	neer if needed)	· · · · · · · · · · · · · · · · · · ·	1	1	Centrifugal 20. Water well contractor's	Other	Sec 1	
						This well was drilled under m	ny jurisdiction and thi	is report	
Topography:						is true to the best of my know Western We11 &	-	245	
Hill						Business name	11.	cense No. 7701	
Slope Upland						Address Box 852, C	S a A.	114177 18	
Valley						Signed Authorized rep	presentative Date	∅ ₹ 	