

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Thomas</u>		<u>NE 1/4 SW 1/4 SW 1/4</u>	<u>20</u>	T <u>9</u> S	R <u>31</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>7 East - 3 South 1/4 East of Mingo</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #:		Application Number:			
City, State, ZIP Code:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>160</u> ft. ELEVATION: <u>80</u> ft.			
		Depth(s) Groundwater Encountered 1. <u>80</u> ft. 2. <u>80</u> ft. 3. <u>80</u> ft.			
		WELL'S STATIC WATER LEVEL <u>80</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was <u>20</u> gpm: Well water was <u>160</u> ft. after <u>9</u> hours pumping <u>20</u> gpm			
		Bore Hole Diameter <u>9</u> in. to <u>160</u> ft. and <u>160</u> in. to <u>160</u> ft.			
		WELL WATER TO BE USED AS:			
		<input checked="" type="checkbox"/> Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) <input type="checkbox"/> 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No <u>X</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>
<u>2</u> PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <u>X</u>
			7 Fiberglass		Threaded <u>X</u>
Blank casing diameter <u>5</u> in. to <u>160</u> ft. Dia					
Casing height above land surface <u>12</u> in. weight <u>250</u> lbs./ft. Wall thickness or gauge No. <u>250</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
<u>1</u> Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:					
From <u>80</u> ft. to <u>160</u> ft.		From <u>160</u> ft. to <u>160</u> ft.			
GRAVEL PACK INTERVALS:					
From <u>80</u> ft. to <u>160</u> ft.		From <u>160</u> ft. to <u>160</u> ft.			
6 GROUT MATERIAL:					
<u>1</u> Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From <u>0</u> ft. to <u>30</u> ft.		From <u>30</u> ft. to <u>160</u> ft.			
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	<u>Creek</u>
Direction from well?		<u>South</u>		How many feet? <u>200</u>	
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0 18 Topsoil					
18 41 Sandy Clay					
41 67 M Gravel					
67 90 Sandy Clay					
90 112 M Gravel					
112 125 Gravel					
125 134 M Gravel					
134 150 Sandy Clay					
150 159 Gravel					
159 160 Ochre					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, <u>(2)</u> reconstructed, or <u>(3)</u> plugged under my jurisdiction and was completed on (mo/day/year) <u>4-3-90</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>376</u> This Water Well Record was completed on (mo/day/yr) <u>6-20-90</u> under the business name of <u>B & B Drilling</u> by (signature) <u>Joseph Beckman</u>					