USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY

EW sec 1/4 1/4 1/4 No.

PRINT CLEARLY.	POLICE A DESCRIPTION OF STREET		WATER WELL KSA 82a-120)				Kansas State Dept. Of Health Water Well Contractors)		
<u> </u>									Forbes-Bldg. 740 Fopeka, Kansas 66620		
1 Location of well:	County	Township name	Fraction		Sectio	n number	V	Town number	Range number		
E CONTROL OF THE PROPERTY OF T	Thomas	North Ranadal			<u></u>	3		9	3 2		
Distance and direction from nearest town or city: 9miles East; 6½miles From Colby Street address of well location if in city: Ad						^{well:} Clarence Cersovsky					
Street address of well location if in city: Address					ess:	Colb	1by, Kansas 67701				
Locate with "X" in section below: Sketch map:							4 Well depth: 157 ft. Date of completion $1/15/76$ Well diameter 36 in.				
W							5				
							Thr	7 Casing: Materia Stee Height: above/bbldwl Threaded Welded Surface 12 in. Diam. Weight lbs./ft			
2								6 in. to 8.7 ft. depth in. to ft. depth	Drive shoe? Yes No		
	Ту	pe and color of material			From	То	8 Scr	8 Screen: Manufacturer Brown: 10' Cook			
Clay					0	46	Typ	e Regular	Dia. 16"		
Sandy clay					46	55	S la Set	Slot/gauze 10% Length 60 Set between 87 ft. and 47 ft. 157			
Coarse sand & gravel					5 5	63	Fittings: 1/2 Gravel pack 1/2 Yes 1/2		X5/8;50% #1 Size range of material —		
Clay & sandy clay					63	80	9 Sta	tic water level:	ce Date <u>01-1</u> 6-76		
Medium to coarse sand					80	95		nping level below land su	orfaces: s. pumping <u>433</u> g.p.m.		
Clay					95	111			s. pumping g.p.m.		
Coarse sand and grave1					111	119	11 Wa	ter sample submitted:	ite		
C1ay					119	121		Il head completion:	_12		
Coarse sand & gravel					121	131	13 We	Pitless adapter \(\sum_{\text{inches above grade}} \) 13 Well grouted? \(\sum_{\text{Yes}} \) \[\sum_{\text{Ves}} \) \[\sum_{\text{Ves}} \sum_{\text{Ves}} \sum_{\text{Ves}} \)			
Medium to coarse sand & clay streaks				s	131	137	De	\square Neat cement \square Bentonite \square			
Clay					137	141		14 Negrest source of possible contamination: ft.4000 DirectionWest Type Fa			
Medium to coarse sand & gravel & clay								II disinfected upon comp		w	
streak	S				141	149		np: Inufacturer's name F1 odel number	Oway 2-9-76	N N	
Coarse sand & gravel					149	156	Lei	Length of drop pipe 150 ft. capacity g.m			
Ochre & Shale					156	165		Submersible	O'' DKL bow1		
	· (u	se a second sheet if needed)						Jet Certrifugal	Reciprocating Other	M	
16 Remarks: elevat	ión	5 Ro	CK 156	•			1	iter well contractor's cert is well was drilled under		1	
Topography:	ar year	-	•				rep	ort is true to the best of	my knowledge and belief. and Pump 245	m	
							D		52 Colby, Ks	69	
☐ Slope XX Upland ☐ Valley							Sig	gned Authorized repre	12 Date 3/32/	76 W	
	e-5									**	