


LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Thomas	SE 1/4 NW 1/4 SE 1/4	25	T 9 S	R 32 E/W

Distance and direction from nearest town or city street address of well if located within city?

9 East 11 South 1/2 North of Colby

WATER WELL OWNER:	Kenneth Englehardt	Murfin Drilling
RR#, St. Address, Box # :		Box 661
City, State, ZIP Code :	Mingo, KS	Colby, KS 67701
		Board of Agriculture, Division of Water Resources
		Application Number: T88-275

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 206 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 112 ft. below land surface measured on mo/day/yr 6-2-88
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to 206 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued .. X .. Clamped ..
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded ..
			Threaded ..
Blank casing diameter 4.5 in. to 186 ft., Dia			ft., Dia
Casing height above land surface 18 in., weight 2.38 lbs./ft.			Wall thickness or gauge No. 0.248

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass
2 Brass	4 Galvanized steel	6 Concrete tile
		8 RMP (SR)
		9 ABS
		11 Other (specify) ..
		12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) ..

SCREEN-PERFORATED INTERVALS:	From 186 ft. to 206 ft., From	ft. to	ft.
	From	ft. to	ft.
GRAVEL PACK INTERVALS:	From 20 ft. to 206 ft., From	ft. to	ft.
	From	ft. to	ft.

GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 20 ft., From	ft. to	ft.	ft. to

What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy
2 Sewer lines	5 Cess pool	8 Sewage lagoon
3 Watertight sewer lines	6 Seepage pit	9 Feedyard
		11 Fuel storage
		12 Fertilizer storage
		13 Insecticide storage
		15 Oil well/Gas well
		16 Other (specify below)
		Plugged

Direction from well? North	How many feet? 120				
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Surface			
3	43	Clay			
43	78	Coarse Sand			
78	98	Clay			
98	108	Medium Sand			
108	110	Clay			
110	118	Medium Sand			
118	143	Clay & Caliche			
143	147	Sand			
147	150	Caliche			
150	157	Clay			
157	159	Medium Sand			
159	196	Clay & Caliche			
196	202	Medium Sand			
202	210	Ochre			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-2-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 394 This Water Well Record was completed on (mo/day/yr) 6-29-88 under the business name of Woofert Pump & Well by (signature) [Signature]
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.