

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Thomas</u>	<u>SE 1/4</u> <u>SE 1/4</u> <u>SE 1/4</u>	<u>24</u>	<u>T 9 S</u>	<u>R 33 W E/W</u>

Distance and direction from nearest town or city street address of well if located within city?

N/A - LOCATION CONFIRMED BY GMD #4

WATER WELL OWNER: Lloyd G. & Bertilla M. WilsonR#, St. Address, Box #: Rt 2

Board of Agriculture, Division of Water Resources

City, State, ZIP Code: Colby, KS 67701

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION:Depth(s) Groundwater Encountered 1. 90 ft. 2. 90 ft. 3. 90 ft.WELL'S STATIC WATER LEVEL 90 ft. below land surface measured on mo/day/yrPump test data: Well water was 90 ft. after 90 hours pumping 90 gpmEst. Yield 90 gpm: Well water was 90 ft. after 90 hours pumping 90 gpmBore Hole Diameter 90 in. to 90 ft., and 90 in. to 90 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes 90 No 90; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes 90 No 90

TYPE OF BLANK CASING USED:

5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 90 Clamped 906 Asbestos-Cement 9 Other (specify below) Welded 907 Fiberglass Threaded 90Blank casing diameter 90 in. to 90 ft., Dia 90 in. to 90 ft.Casing height above land surface 90 in., weight 90 lbs./ft. Wall thickness or gauge No. 90

TYPE OF SCREEN OR PERFORATION MATERIAL:

7 PVC 10 Asbestos-cement

11 Steel 8 RMP (SR) 11 Other (specify) 90

2 Brass 4 Galvanized steel 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

5 Gauzed wrapped 8 Saw cut 11 None (open hole)

6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify) 90SCREEN-PERFORATED INTERVALS: From 90 ft. to 90 ft., From 90 ft. to 90 ft.From 90 ft. to 90 ft., From 90 ft. to 90 ft.GRAVEL PACK INTERVALS: From 90 ft. to 90 ft., From 90 ft. to 90 ft.From 90 ft. to 90 ft., From 90 ft. to 90 ft.

GROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 Other 90Grout intervals: From 90 ft. to 90 ft., From 90 ft. to 90 ft.

What is the nearest source of possible contamination:

10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 12 Fertilizer storage 16 Other (specify below) 90

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		ENTER			Removed upper 3ft. casing
		PLUGGING	110	100	sand
			6	3	cement
			3	0	surface dirt
		INFORMATION			
		AT			
		RIGHT			

RECEIVED

JUL 03 1989

DIVISION OF

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-21-89 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 90 This Water Well Record was completed on (mo/day/yr) 90under the business name of 90 by (signature) Lloyd G. Wilson