


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

Sent 3-28-77
WINONA NE
WATER WELL RECORD
KSA 82a-1201-1215
ADD ABD

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Thomas	Fraction SE 1/4 SE 1/4 NW 1/4	Section number 28	Township number T 9 S R 33 E	Range number 33 E
2. Distance and direction from nearest town or city: 8/5 25 E fr I70 Inter change AT Colby, KS		3. Owner of well: Harold Herbel R.R. or street: Rt 2 City, state, zip code: Colby, Ks. 67701				
4. Locate with "X" in section below: 		Sketch map:		6. Bore hole dia. 6 in. Completion date 2-23-77 Well depth 285 ft.		
5. Type and color of material		From	To	7. ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☒ Reverse rotary		
Topsoil, brown, Clay silty, Clay, brown		0	130	8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☒ Stock ☐ Lawn ☐ Oil field water ☐ Other		
Fine Sand, brown, Streak Sandy clay		130	150	9. Casing: Material PVC Height: Above or below Threaded ☐ Welded ☒ Surface ☐ in. RMP ☐ PVC ☐ Weight 2.7 lbs./ft. Dia. 5 in. to 285 ft. depth Wall Thickness: inches or Dia. ☐ in. to ☐ ft. depth gage No. 258 MHC		
Fine Sand, brown, Med Gravel, Brown		150	159	10. Screen: Manufacturer's name Nab Plastics (PVC) Type 5105 Dia. 5" Slot/gauze ☐ Length 17 Set between 265 ft. and 285 ft. ft. and ☐ ft. Gravel pack? yes Size range of material 4-4		
Sandstone, white		159	160	11. Static water level: ☐ mo./day/yr. 434 ft. below land surface Date 1-23-77		
Med Gravel, brown		160	168	12. Pumping level below land surfaces: 276 ft. after 6 hrs. pumping 30 g.p.m. ☐ ft. after ☐ hrs. pumping ☐ g.p.m. Estimated maximum yield 30 g.p.m.		
Fine sand, brown, Streaks Sandy Clay		168	180	13. Water sample submitted: ☐ Yes ☒ No Date ☐		
Fine sand, brown, Streaks sand stone		180	212	14. Well head completion: 12" MHC ☒ Pitless adapter ☐ 6" inches above grade		
Sandy clay, brown		212	219	15. Well grouted? yes With: ☐ Neat cement ☒ Bentonite ☐ Concrete Depth: From 0 ft. to 10 ft.		
Fine Sand, brown, Med Gravel, brown		219	234	16. Nearest source of possible contamination: ft. 500 Direction N Type Cess pool Well disinfected upon completion? ☐ Yes ☒ No		
Sandy clay, brown		234	248	17. Pump: ☐ Not installed Manufacturer's name Gould Model number 25 EL HP 2 Volts 230 Length of drop pipe 180 ft. capacity 30 g.p.m. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other		
Fine Sand, brown, streaks sandy clay		248	268	20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Red Tiger Fire 125 Business name License No. Address Box 524 Colby, KS Signed Joe P. ... Date 3-14-77 Authorized representative		
Fine Sand, brown, Med Gravel, brown		268	276			
Ochre, yellow, Shale, blue		276	285			
BROCK 276'						
(Use a second sheet if needed)						
18. Elevation: Topography: ☐ Hill ☐ Slope ☒ Upland ☐ Valley		19. Remarks: 3158 (TOPO) 3162				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5