

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: THOMAS	SW 1/4 NE 1/4 NE 1/4	33	T 9 S S	R 33 W EW

Distance and direction from nearest town or city street address of well if located within city?

SS SW of Mingo

WATER WELL OWNER:	WARRIOR DRILLING	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	151 N. MAIN SUITE 700	Application Number: T 82-107
City, State, ZIP Code :	WICHITA, KS. 67202	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL: 288 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 140 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 140 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 35 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 288 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 278 288 ft., Dia			Threaded
Casing height above land surface 12 in., weight 250 lbs./ft. Wall thickness or gauge No. 250			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 278 ft. to 288 ft.	From ft. to ft.	From ft. to ft.
GRAVEL PACK INTERVALS:	From ft. to ft.	From ft. to ft.	From ft. to ft.

GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From 0 ft. to 20 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? West				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				Draw
				How many feet? 1000

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	20	Topsoil	198	217	Fine Sand
20	34	M. Gravel	217	230	M. Gravel
34	55	Sandy Clay	230	256	Sandy Clay
55	67	M. Gravel	256	271	M. Gravel
67	88	Sandy Clay	271	288	Ochre
88	100	M. Gravel			
100	112	Sandy Clay			
112	132	Sandy Clay			
132	148	M. Gravel			
148	152	Sandy Clay			
152	156	M. Gravel			
156	167	Sandy Clay			
167	174	M. Gravel			
174	195	Sandy Clay			
195	198	M. Gravel			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-10-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 376 This Water Well Record was completed on (mo/day/yr) 5-82 under the business name of B & B DRILLING by (signature) Joseph Beckman
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.