USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

## REPLACEMENT WELL

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County Fraction		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Section number		Township number	Range number		
1. Location of well:	Thomas	NW 1/4 SE 1/4 SW	1/4	36		т 9 ѕ	R 33	<b>X</b> /w	
3 3/4 South; ¼ East  R.R. or s				er of well: Delton Hubert					
4. Locate with "X" in section below:  Sketch map:				tate, Alb o	code: I	6. Bore hole dia 36 in Well depth 270 ft.		13-76	
						7Cable toolRotary Driven DugHollow rod Jetted Bored X Reverse rotary  8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Oil field water Other  9. Casing: Material Steel Height: Above or X In.  7. Threaded Welded X Surface In.  8. Use: Domestic Public supply In.  9. Casing: Material Steel Height: Above or X			
5. Type and color of material				From	То	Diain. to ft. depth gage No			
Top Soil				0	45	Brown Type Regular			
Coarse Sand and Gravel				45	89	Slot/gauze 10%	Length 100 t	Aller and the second se	
Clay				89	111	10 Cook 260 ft.  Gravel pack? X Size ro	and 2/0'	ft. 5/8 50% i	#1
Coarse Sand and Gravel				111	129	11. Static water level: mo./day/yr. 140 ft. below land surface Date 7-9-76			
Clay				129	134	12. Pumping level below lan 220 ft. after2	d surfaces:		
Coarse Sand and Gravel				134	159	ft. after hrs. pumping g.p.m.  Estimated maximum yield 750 g.p.m.			
Clay				159	167	13. Water sample submitted: mo./day/yr.  Yes X No Date			
Coarse Sand and Gravel				167	199	14. Well head completion:			
Clay and Mix Sand				199	218	Pitless adapter 12 Inches above grade  15. Well grouted? X Clay			
Coarse Sand and Gravel				218	224	With: Neat cement X Bentonite X Kanketek   Depth: From 0 ft. to 10 ft.			
Sand Stone				224	225	16. Negrest source of possible contamination: ft. 2600 Direction NNW Type Farm			
Clay			225	237	Well disinfected upon completion? Yes X No			<u>"</u>	
Med. Sand			237	250	17. Pump:  Manufacturer's name <u>US</u> 6  Model number		~	W	
C1ay			250	254	Length of drop pipe		No. of the Party	S) m	
Sandy Clay Coarse Sand and Gravel			254 263	263 270	Type: Submersible	XX Turbine			
Shale	(Use a second s	heet if needed)	······································	270	280	Jet Centrifugal	Recipro	Sec	N
18. Elevation:	19. Remarks:	ROCK Z70				20. Water well contractor's This well was drilled under r		1 '	5
Topography:						is true to the best of my know Western Well		<u>245</u> ≩	Contraction of Spirite
HIII Slope						Rusinass nama		7701° =	E.
X Upland Valley						Signed Dally Signed Signed Authorized re	presentative Date	1-15-76	2 N N
Forward the white, bl	ue and pink copies to the Department	of Health and Environment					Form WV	/C-5	1.