WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

Township - Summers

	County	Fraction		Section	number	Township number	Range number		
1. Location of well:	Thomas	SE 1/4 SE 1/4 NW	1/4	5		T 9 s	R 34	E <b>!</b> /W	
2. Distance and direction from nearest town or city: From Colby, Ks. 3. Owner of well: William Keck									
$5\frac{1}{2}$ miles South; $4\frac{1}{2}$ miles West R.R. or street:									
City, state, zip code: COIDY, Kan								Name and Address of the Address of t	
4. Locate with "X" in section below:  Sketch map:					6. Bore hole dia. 30 in. Completion date				
					ŀ	7. Cable tool Rotary Driven Dug			
						Hollow rod Jetted Bored X Reverse rotary			
					Ī	8. Use: Domestic Public supply Industry			
w   1						X Irrigation Air conditioning Stock			
SW SE					ŀ	LawnOil field waterOther 9. Casing: Material Stee Height: Above of blight			
						Threaded Welded Surface in.			
S					RMPIbs./ft.				
1 Mile				_		Dia.16 in. to 176t. depth Wall Thickness: inches or Dia in. to ft. depth gage No. 0 188			
5. Type and color of material				From	То	10. Screen: Manufacturer's name Brown			
Top soil				1 1	10	TO COOK			
Clay					73	Type Regular Dia. 16" Slot/gauze 10% Length 80			
Medium to coarse sand & clay streaks					85 114	Set between 176 ft. and 256 ft.			
Coarse sand & gravel				114		$\frac{256}{\text{Gravel pack?}} \frac{\text{ft. and}}{\text{Size range of material}} \frac{266}{\text{$1.5000}} \frac{\text{ft. and}}{\text{$1.5000}} \% \# 1$			
Clay					132				
Coarse sand & gravel				132	143	11. Static water level: 174 ft. below land surface Date 1/27/76			
Clay Coarse sand & gravel				143	146	12. Pumping level below land surfaces:			
Sandy clay				155		250 ft. after 2 hrs. pumping 1515g.p.m.			
Coarse sand & gravel				163	167	ft. after hrs, pumping g.p.m.  Estimated maximum yield g.p.m.			
Coarse sand & gravel				168		13. Water sample submitted: mo./day/yr.			
						Yes X No Date			
Cement-hard				184		14. Well head completion: Pitless adapter 12 Inches above grade			
Coarse sand & gravel				186	198	16 Wall arranged X			
Clay				1.00	0.1.0	With: Neat cement X	Bentonite X Conc	ay	
Clay				198		Depth; From O ft. to 10 ft.			
Coarse sand & gravel& clay streaks				213	228	16. Negrest source of possible contamination: ft. 2800 Direction NW Type Farm			
Medium to coarse sand				228	242	Well disinfected upon completion? Yes X No			
<del></del>						17. Pump:	Not installed 3	3/16 , (4)	
Coarse	sand & gravel			242	264	Manufacturer's name Bryco	n Jackson	- 1	
Ochre & Shale				264	280	Model Holliber			
ASSESSED PACK 714						Type: 7 stage 1	2" GH bow1	o.m.   \$\frac{\xi}{2}m	
						Submersible Jet	X Turbine Reciprocati		
1	(Use a second sl	neet if needed)				Centrifugal	Other	ng   Sec	
18. Elevation: 19. Remarks:						20. Water well contractor's o	ertification:		
						This well was drilled under my		ort	
Topography:						is true to the best of my know Western Well		45 \$15	
						business name License No.			
Slope Stope						Address 3/22/7/			
X Optana Valley						Signed Authorized rep	Date dan	\$ 12 PT	
Form WWC-5									