WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

Township - Summers

	County	Fraction		Section number		Township number Range number			
1. Location of well:	Thomas	SE 1/4 NW 1/4 NW	1/4		9	т 9 s	R 3.4	EI/W	
					3. Owner of well: Joe McIlnay				
8+蘇¼ miles South: 3-3/4 Miles West Street address of well location if in city:			R.R. or street: RFD						
				tate, zip o	ode: C O	1by, Kansas 67701			
4. Locate with "X" in section below: N						6. Bore hole dia 3 0 in. Completion date Well depth 2 3.8 ft. 1 / 2 3 / 7 6			
						7Cable toolRotaryDrivenDug			
xx xe						Hollow rod Jetted Bored X Reverse rotary			
₩						8. Use:Domestic Public supply Industry X			
SW SE					9. Casing: Material S. t. a. Theight: Above of boldwy-				
					Threaded Welded A Surface 12 in.				
\$						RMP PVC Weight 31.66 lbs./ft.			
1 Mile				From	То	Dia. 1.6 in. to 148ft. depth Wall Thickness: inches or Diain. to ft. depth gage No			
5. Type and color of material				11011	10. Screen: Manufacturer's name Brown				
01 0 1 0 1				0	1 / E	<u>IU COOK</u>			
Clay & sand streaks				╁╨┷	145	Slat/amore 10% longth 801			
Fine to coarse sand & gravel				145	155	Set between 148			
Sandy clay & cemented streaks				155	161				
Fine to coarse sand & gravel				161	172	_150_ft. below land surface Date 2/6/76			
Sandy clay				172	178	12. Pumping level below land surfaces: 230 ft. after hrs. pumping 1165g.p.m. ft. after hrs. pumping g.p.m.			
Fine to coarse sand & gravel				178	191	Estimated maximum yield 1165 g.p.m. 13. Water sample submitted: mo./day/yr. Yes X No Date			
Sandy clay				191	201				
Fine to coarse sand & gravel				201	218	14. Well head completion:			
Cemented sand				218	219	Pitless adapter1_2 Inches above grade			
			*******************			15. Well grouted? X	L Y		
Fine to coarse sand & gravel				219	235	15. Well grouted? X With: Neat cement X Depth: From ft. to 10 ft.			
Cemented sandy clay 5ha/c				235	238	16. Nearest source of possible ft. 3900 Direction	ı '		
Fine to coarse sand & gravel				230	266	Well disinfected upon comple			
						17. Pump:	Loway installed 8		
Shale				Z 0 0	270	Model number 7610			
BKOCK 250						Length of drop pipe 220		.p.m.	
						Type: 11 stage	e $10^{"}$ DOH b	YOW L	
and the second s			***************************************	-		Jet	ting		
	(Use a second s	heet if needed)				Centrifugal	Other	—— , , , , , , , , , , , , , , , , , ,	
18. Elevation: 19. Remarks:						20. Water well contractor's This well was drilled under n		port	
Topography:						Western Well and Pump $245 \mid \overline{5} \mid \overline{n}$			
Hill Slope						Business name PO Box 8	52 Colby, k	Se No. 7	
$\frac{X}{X}$ Upland						Signed Dawy Berry Date 312 To			
Valley						Authorized re	presentative	<u> </u>	