

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Thomas</u>	<u>NE 1/4 NE 1/4 NW 1/4</u>	<u>10</u>	<u>T 9 S</u>	<u>R 35 E/W</u>

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: <u>Betty C. Secrest</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>P.O. Box 427</u>	Application Number:
City, State, ZIP Code: <u>Colby KS 67701</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>10</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>8</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: ① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
① Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>4</u> in. to ft., Dia			Threaded
Casing height above land surface <u>8'</u> Below in., weight			lbs./ft. Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	11 Other (specify) <u>NA</u>
1 Steel	3 Stainless steel	6 Concrete tile	9 ABS
2 Brass	4 Galvanized steel		12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) <u>NA</u>
SCREEN-PERFORATED INTERVALS:	From <u>NA</u> ft. to <u>NA</u> ft., From		
	From ft. to ft., From		
GRAVEL PACK INTERVALS:	From ft. to ft., From		
	From ft. to ft., From		

6 GROUT MATERIAL:	1 Neat cement	② Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>10</u> ft. to <u>8</u> ft., From				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				14 Abandoned water well
				15 Oil well/Gas well
				① Other (specify below)
				<u>None Apparent</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
					well had been plugged
					we removed cement
					pad and terminated
					the casing 8' below
					ground level, we cleaned
					the annulus to 10' +
					placed cement grout
					inside casing + annulus
					to 8' then backfilled
					with compacted clay
					+ Topsoil

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-30-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Contractor's License No. This Water Well Record was completed on (mo/day/yr) <u>4-1-92</u> under the business name of by (signature) <u>[Signature]</u>
--