

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County	Fraction	Section number	Township number	Range number
		SHERMAN	N 1/4 SE 1/4 SE 1/4	7	T 9 S	R 37
2. Distance and direction from nearest town or city: Edson				3. Owner of well: LEONARD OWENS		
Street address of well location if in city: 2E 3 3/4 S 1/4 E				R.R. or street: City, state, zip code: Edson Kansas 67733		
4. Locate with "X" in section below: N W E S 1 Mile Sketch map:				6. Bore hole dia. 2 1/2 in. Completion date Well depth 168 ft. 6-23-76		
<p>1 Mile</p>				7. Cable tool Rotary Driven Dug Hollow rod Jetted Bored <input checked="" type="checkbox"/> Reverse rotary		
				8. Use: Domestic Public supply Industry <input checked="" type="checkbox"/> Irrigation Air conditioning Stock Lawn Oil field water Other		
5. Type and color of material				9. Casing: Material Steel Height: Above or below Threaded Welded <input checked="" type="checkbox"/> Surface 12 in. RMP PVC Weight 36 lbs./ft. Dia. 1 1/2 in. to 1 1/8 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 219		
				10. Screen: Manufacturer's name W.A. Brown Type Louver Dia. 16 Slot/gauze 1/8 x 7 Length 50 Set between 118 ft. and 168 ft. Gravel pack? Yes Size range of material 1/4 x 7/8		
M GRAVEL				85	96	11. Static water level: mo./day/yr. 88 ft. below land surface Date 5-7-76
SANDY CLAY, SANDSTONE				96	113	12. Pumping level below land surfaces: 151 ft. after 5 hrs. pumping 1200 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 1200 g.p.m.
M GRAVEL, SANDY CLAY				113	153	13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No Date
SANDY CLAY, SANDSTONE				153	161	14. Well head completion: Pitless adapter inches above grade
M GRAVEL, TRACC CLAY				161	166	15. Well grouted? YES With: Neat cement Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.
Ochre				166	168	16. Nearest source of possible contamination: None ft. Direction Type Well disinfected upon completion? Yes <input checked="" type="checkbox"/> No
						17. Pump: Not installed Manufacturer's name Western Lord Pattern Model number 6 M HP 100 Volts 480 Length of drop pipe 150 ft. capacity 1000 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
(Use a second sheet if needed)						20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. A.H. Dwylling Co Inc 166 Business name License No. Address Goodland Kansas Signed Bill Clifford Date Authorized representative 6-23-76
18. Elevation:		19. Remarks: 3496 (TOPO)				
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley						