		WATER WELL RECORD Form			1 WWC-5 KSA 82a-1212				
1 LOCATION OF WAT	ER WELL:	Fraction		1	ction Number	Township	p Number		Number
County: OTTAWA		NW 1/4		SE 1/4	16	T 9	S	R 4	E/W
Distance and direction	from nearest town o	or city street ac	dress of well if locate	ed within city?					
	881 VICT	ORY RD.			OTTAV	VA COUNTY	PERMIT #	97-209	
WATER WELL OW									
RR#, St. Address, Box		TORY RD.				Board a	of Agriculture, [Division of W	ater Resources
City, State, ZIP Code	· - -		26				•	DIVISION OF VV	iter riesources
1	DELPHOS			1.1. 0			ition Number:		
AN "X" IN SECTION			OMPLETED WELL						
N. X 0201101	De		vater Encountered 1						
ī ! I	ı WE	ELL'S STATIC	WATER LEVEL . 3.5	.8 ft. t	elow land sur	face measured	l on mo/day/yr	8-7-97	,
		Pump	test data: Well wat	erwas	38.4 ft. a	fter 1	hours pu	mping	12 gpm
NW	NE Est		.9. gpm: Well wate						
	Bo	re Hole Diame	ter9in. to	45	ft	and	in	to.	ft
i w			O BE USED AS:	5 Public water		8 Air condition		Injection well	
-	""						•	•	
sw	2EX	1 Domestic				9 Dewatering		Other (Specif	•
1	1	2 Irrigation	4 Industrial				well		
↓	Wa	is a chemical/b	acteriological sample	submitted to D					ımple was sub
5	mit	ted			Wa	ter Well Disinfe	ected? Yes	X No	
5 TYPE OF BLANK C	ASING USED:		5 Wrought iron	8 Concr	ete tile	CASING	JOINTS: Glued	iX Claı	nped
1 Steel	3 RMP (SR)		6 Asbestos-Cement	9 Other	(specify below	v)	Weld	ed	
2 PVC	4 ABS		7 Fiberglass			•	Threa	ded	
Blank casing diameter	5 in	., 34.8	3 # Dia	in to		ft Dia	***************************************	in to	fr
Blank casing diameter Casing height above la	nd aurtage 20	10	in		lba /	II., Dia		"SDR 26	
			in., weight ÷						
TYPE OF SCREEN OF							Asbestos-ceme		
1 Steel	3 Stainless ste	eel	5 Fiberglass		MP (SR)	11	Other (specify)		
2 Brass	4 Galvanized :	steel	6 Concrete tile	9 AB	S	12	None used (op	en hole)	
SCREEN OR PERFOR	ATION OPENINGS	ARE:	5 Gauz	ed wrapped		8 Saw cut		11 None (o	pen hole)
1 Continuous slot	3 Mill sl	lot .035	6 Wire	wrapped		9 Drilled hol	es		
2 Louvered shutte	er 4 Key p	ounched	 7 Torch	ı cut		10 Other (spe	ecify)		
SCREEN-PERFORATE		From 34	.8	ווול ס	ft Fro	• •	ft. to		
CDAVEL DAC	CK INTERVALS:	From. 30	ft. to .	44.8	# Fro	···	ft. to	o	4
GRAVEL FAC	on intremited.							0	
		From	ft. to		ft., Fro			0	
6 GROUT MATERIAL:	1 Neat cem	ent 20	2 Cement grout	_3_Bento	onite 4	Other			• • • • • • • • • •
Grout Intervals: From	n	to 47	ft., From	<i>.</i> ft.	to	ft., From			
What is the nearest so	urce of possible con	tamination:			10 Lives	tock pens	14_A	bandoned wa	ter well
1 Septic tank	4 Lateral li	nes	7 Pit privy		11 Fuel	storage	15 O	il well/Gas w	ell
2 Sewer lines	5 Cess poo	ol	8 Sewage lag	oon	12 Fertili	izer storage		ther (specify	
3 Watertight sewe	er lines 6 Seepage	pit	9 Feedyard		13 Insec	ticide storage	TO BE PLU	GCED BY	OWNER
Direction from well?	NORTHEAST		, .		How ma		15		
FROM TO		LITHOLOGIC I	OG	FROM	TO 1	ily leet:	PLUGGING II	NTERVALS	
6 1	ROAD GRAV			111011	'				
	CLAY SILT	77766	DDUIM		-				
1 18 18 29	CLAY SILT		DITOWN		+				
					 				
29 43	SAND FINE								
43 45	CLAY GRAY								
					1				
		77.340							
	W			1:	† †				
					 				
					+	AND THE RESIDENCE OF THE PARTY			
					 				
					.		NATURE OF THE STATE OF THE STAT		
					<u> </u>				
Z CONTRACTORIO O	D I ANDOMATERIO	CERTIFICATI	NI. This4				0) =	lar medical-at	
			ON: This water well w						
completed on (mo/day/y	/ear)							wledge and	belief. Kansas
Water Well Contractor's			This Water V	Vell Record wa	s completed		11111		M
under the business nan	ne of PESTINGER	PUMP SE	RVICE		by (signat	tura Qu		rung	
			RMLY and PRINT clearly. Pli- -0001. Telephone: 913-296-						Department