USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

RULETA

## WATER WELL RECORD KSA 82a-1201-1215

BAR

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)
Topeka, Kansas 66620

17 10			
County Fraction  1. Location of well:	Section number		Township number Range number
Sherman NW 1/4 NE 1/4 NW 1/4	:	3	т 9 s r 41 W E
· · · · · · · · · · · · · · · · · ·	ner of wel	l: Ed	Danills
3/4 mile West of Ruleton, Kansas  R.R. or street: Street oddress of well location if in city:		. ~	
		code: G	oodland, Kansas 67735  6. Bore hole dia. 30 in. Completion date 11-24-75
4. Locate with "X" in section below:  Sketch map:			Well depth 270 ft.
NW \( \frac{1}{4} \), NE \( \frac{1}{4} \), NW \( \frac{1}{4} \)  Sec. 3, Twp. 9, Rge. 41 W		7Cable toolRotaryDrivenDug	
		Hollow rod Jetted Bored X_Reverse rotary	
			8. Use: Domestic Public supply Industry
		X_ Irrigation Air conditioning Stock	
SW SE			LawnOil field waterOther  9. Casing: MaterialStee_Height: Above tellow
<u> </u>	*		Threaded Welded X Surface 12 in.
\$			RMPPVCWeight36lbs./ft.
t → 1 Mile → I	Τ.	T -	Dia. 16n. to 270ft. depth Wall Thickness: inches or Diain. to ft. depth gage No219
5. Type and color of material	From	То	10. Screen: Manufacturer's name
alay and atropic hard real-		3.20	W. A. Brown
clay, sand streaks, hard rock	10	132	Type
medium sands	132	138	Set between 170 ft. and 270 ft.
very sandy clay	128	158	ft. andft.
very bandy cray			Gravel pack? <u>VCS</u> Size range of material 3/8  11. Static water level: mo./day/yr.
good fine	158	162	11. Static water level: mo./day/yr.  151 ft. below land surface Date 2-3-76
sandy clay and rock	162	182	12. Pumping level below land surfaces:
			205 ft. after 8 hrs. pumping 655 g.p.m. hrs. pumping g.p.m.
medium to good loose and clean	182	186	Estimated maximum yieldg.p.m.
streaks sand rock clay and sand	186	211	13. Water sample submitted: no mo./day/yr.
	017	200	Yes No Date
medium to good light streaks rock	15TT	228	14. Well head completion:  Pitless adapter
XXXX rock	228	232	15. Well grouted? Ves
good to medium loose and clean	222	240	With: X Neat cement Bentonite Concrete
BAAA OO HIGHTAIN TOODE BILL CTEBIL			Depth: FromO ft. tolO_ ft.
clay and rock	240	241	16. Nearest source of possible contamination: none ft Direction Type
fine sand loose and clean	241	262	Well disinfected upon completion? Yes No
			17. Pump: Not installed
soapstone	262	265	Manufacturer's name Byron Jackson  Model number Turbine HP 100 Volts
blue	265	270	Length of drop pipe 260 ft. capacity 600g.p.m.
12:00			Туре:
	+	<b> </b>	Submersible Turbine Reciprocating
(Use a second sheet if needed)			Centrifugal Other
18. Elevation: 19. Remarks:			20. Water well contractor's certification:
72 191 1 101			This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
7/10			is now to the pest of my knowledge and petter.
Topography:			Northwest Drilling Co. Inc.
HILL STATE OF THE			Northwest Drilling Co., Inc.  Business name  License No.