USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

RUKI.

WATER WELL RECORD KSA 82a-1201-1215

BBD

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

	12/20					Topeka, Kansas 00020
County 1. Location of well:	Fraction NW		ection :	number	Township number	Range number
Sherian of well: Sherian	5 1/4 1 1/4 NO	1/4	10		т 9	s R 4/ 2/W
2. Distance and direction from nearest town or city:		3. Owner			AYGAN US	TMCYCR
Street address of well location if in city: 3/45/	1/2 P	R.R. or str			80x 532	
	7 E	City, state	, zip c	ode:	Colby KAR	
4. Locate with "X" in section below: S N	ketch map:				6. Bore hole dia 252 f	- in . Completion date
ŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢŢ				ļ	7 Cable tool Ro	
1× NE					Hollow rod Jet	· · · · · · · · · · · · · · · · · · ·
₩					8. Use: Domestic	_ Public supply Industry
*						_ Air conditioning Stock
SW SE				ŀ		Oil field water Other
			•		Threaded Welded _	
\$					RMP PVC	Weightlbs./ft.
1 Mile ————————————————————————————————————		т			Dia. Le in. to La ft.	depth Wall Thickness: inches or depth gage No.
5. Type and color of material			From	То	10. Screen: Manufacture	
M GRAVEL SANdy CLAY		T_{i}	ν 2	125	Wy At BOOK	UN
I JANUCK, SANCY CLAY		-	<i>U.</i> 3	130	Type LOUVER Slot/gauze 18 1 7	Dia. <u>//</u> Length <u>// /</u>
M GRAUCL		<u> </u>	30	148	Set between 82	ft. andft.
FINE SAND, MGRAUEL SA	Ndu Clar	/	48	180	Gravel pack? 45 Siz	ft. andft.
, ,	7-59-59-49	ľ	GA	182	11. Static water level:	_mo./day/yr.
M GRAUCL			80	105	109 ft. below land	i surface Date <u>4-15-76</u>
SANDY CLAY, SANDSTONE		/	83	190	12. Pumping level below	land surfaces: hrs. pumping
Fire Spard M Gonzal	SANdSTONE		90	210		hrs, pumping g.p.m.
1 2 114 2			70	270	Estimated maximum yield	g.p.m.
tive SAND, 19 GRAVEL, S	Sandy Chay	2	10	248	13. Water sample submitt	
Ocher	,		248	251	Yes No	Date
Late of the	egy)		20		Pitless adapter	Inches above grade
A Section 1997	<u> </u>				15. Well grouted? 40	হ
					With: Neat cement Depth: From ft.	Bentonite X Concrete
					16. Nearest source of pos	
					ft Direction	Type NONC
					Well disinfected upon co	mpletion?YesX No
					17. Pump: Manufacturer's name	Les Tern LAND Rolled
					Model number	M HP 80 Volts
					Length of drop pipe	90 ft. capacity 500 g.p.m.
					Type: Submersible	Turbine
					Jet	Reciprocating
(Use a second sh	eet if needed)				Centrifugal	Other
18. Elevation: 19. Remarks:	1000				20. Water well contracto	
3993	(luto) 1				This well was drilled und is true to the best of my l	er my jurisdiction and this report knowledge and belief.
Topography:	2				SHADuller	460 hrc. 166
— Hill — Slope	J				Business name	License No.
X Upland					Address Bill (1)	Stoud
Valley					Signed Authorized	representative 3 Date 76