USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PAINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215
RCR

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

			Topeka, Kansas 66620
1. Location of well: SHERMAN	Fraction NW 1/4 NW 1/4 NW 1/4	Section number	Township number Range number
2. Distance and direction from nearest town or city:	170 10 1/4 /V W 1/4 /V /U/1/4	ner of well: F/T)	T S R H/ EN
Street address of well location if in city: OF B	CODIANIO R.R.O	or street: R	6. Bore hole dia 22 in. Completion date 1-27:
4. Locate with "X" in section below:	Sketch map:	:	6. Bore hole dia 26 in. Completion date 1-27.16 Well depth 322 ft.
X	F	-	7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary 8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock
S 1 Mile ————————————————————————————————————			LawnOil field water Other 9. Casing: Material Meight: Above or below Threaded Welded Surface in. RMP PVC Weight T lbs./ft. Dia / in. to ft. depth Wall Thickness: inches or
5. Type and color of material		From To	10. Screen: Manufacturer's name 11/31, RROWN
Top Soil		0 - 3	Type M1 1/50 / T Dia. 16 11
(lay Gravel & Sandstone		3 135	Slot/gauze
Gravel		135 141	Gravel pack? X Size range of material 1/2
Sandyclay		141 160	11. Static water level: mo./day/yr.
Gravel		160 171	12. Pumping level below land surfaces: 12. Pumping level below land surfaces: 13. Pumping 800 g.p.m.
(lay & Sandstone		171 215	Tee ft. after 16 hrs. pumping 1200 g.p.m. Estimated maximum yield 1200 g.p.m.
(lay & Gravel		215 223	13. Water sample submitted: mo./day/yr. Yes No Date
Gravel	- TIND	223 246	14. Well head completion:
Sandstone & Clay		246 255	Pitless adapter inches above grade 15. Well grouted?
Gravel (12 (12)	255 276	With: Neat cement Bentonite \(\frac{1}{2} \) Concrete Depth: From \(\frac{1}{2} \) ft. to \(\frac{1}{2} \) ft. \(\frac{1}{2} \) ft. \(\frac{1}{2} \) ft.
(lay & Sandstone (276 297	16. Nearest source of possible contamination: ft Direction Type
Gravel (c) Soapestone		297 319	Well disinfected upon completion? Yes No
Soapestone	Charles Comments	319 320	17. Pump: Manufacturer's name Arc Third
Shale	CE SIMES	320 326	Model number 12 HCC/// HP Volts Length of drop pipe 3/0 ft. capacity 200g.p.m.
1200 3			Type: Submersible Turbine
(Use a second	sheet if needed)		Jet Reciprocating Centrifugal Other
18. Elevation: 19. Remarks: Topography: Hill Slope Upland	524 (TUPO)		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. The structure of the service of
Valley Forward the white, blue and pink copies to the Department			Authorized representative: Form WWC-5