

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Riley Fraction SE 1/4 NW 1/4 SE 1/4 Section Number 36 Township Number T 9 S Range Number R 6 NW Distance and direction from nearest town or city street address of well if located within city? 7308 Anderson Ave Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: 39.22576 Longitude: 96.71004 Elevation: 1194 Datum: WGS 84 Data Collection Method: Hand Held

2 WATER WELL OWNER: Jeff Smith RR#, St. Address, Box #: 7308 Anderson Ave City, State, ZIP Code: Kearns KS 66502

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: N W E S 4 DEPTH OF COMPLETED WELL: 255 ft. Depth(s) Groundwater Encountered (1) 255 ft. (2) - ft. (3) - ft. WELL'S STATIC WATER LEVEL: - ft. below land surface measured on mo/day/yr. Pump test data: Well water was 255 ft. after - hours pumping - gpm Est. Yield: - gpm Well water was - ft. after - hours pumping - gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Ground Source

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass HDPE CASING JOINTS: Glued Clamped Welded Threaded Blank casing diameter 3.1 in. to 255 ft., Diameter. 60 in., Weight lbs./ft. Wall thickness or gauge No. SDR 11 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From - ft. to - ft., From - ft. to - ft., From - ft. to - ft. GRAVEL PACK INTERVALS: From - ft. to - ft., From - ft. to - ft., From - ft. to - ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other Grout Intervals: From 255 ft. to 0 ft., From - ft. to - ft., From - ft. to - ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well House 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/gas well Direction from well? W.S.T. How many feet? 20

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-18 Soil Clay, 18-25 Limestone, 25-120 Alt Shale, 120-126 Limestone, 126-182 Alt Shale, 182-191 Limestone, 191-255 Alt Shale.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/11/09 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 760 This Water Well Record was completed on (mo/day/year) 7/15/09 under the business name of Associated Drilling Inc by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.