



Dual Compensated Porosity Log

DIGITAL LOG (785) 625-3858

API No.

15-145-21,582-00-00

Company Murfin Drilling Company, Inc.

Well Fisher 'C' No.1-33

Field Wildcat

County Pawnee

State Kansas

Location 1050' FNL & 1850' FWL

Sec: 33

Twp: 22S

Rge: 15W

Other Services
DIL
MEL/BHCS

Permanent Datum Ground Level Elevation 2003

Log Measured From Kelly Bushing 5 Ft. Above Perm. Datum

K.B. 2008
D.F.
G.L. 2003

Date 3/14/2009

Run Number One

Type Log CNL / CDL

Depth Driller 4150

Depth Logger 4149

Bottom Logged Interval 4128

Top Logged Interval 1900

Type Fluid In Hole Chemical

Salinity, PPM CL 6,700

Density 9.1

Level Full

Max. Rec. Temp. F 118

Operating Rig Time 5 Hours

Equipment -- Location 15 Hays

Recorded By C. Desaire

Witnessed By Terry McLeod

Borehole Record

Casing Record

Run No	Bit	From	To	Size	Wgt.	From	To
1	12.25	00	621	8.625	24#	00	621
2	7.875	621	4150				

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Thank you for using Log-Tech, Inc.
(785) 625-3858

Larned, S to 19 Hwy, 6 E to 50th Ave,
4 S, 1/2 E, S Into

Database File: c:\warrior\data\murfin_fisher c #1-33\murfin2hd.db
Dataset Pathname: dil\mrfnstc
Presentation Format: cdl
Dataset Creation: Sat Mar 14 13:12:16 2009
Charted by: Depth in Feet scaled 1:600

0	Gamma Ray	150	30	Compensated Density (pu)	-10	
6	Caliper (in)	16	2	Bulk Density (g/cc)	3	
			15000	Line Tension (lb)	0	
				-0.25	Correction (g/cc)	0.25
					LSPD	(ft/min)































