



DIGITAL LOG (785) 625-3858

Dual Compensated Porosity Log

15-023-21,333-00-00

API No.

Company Credo Petroleum Corporation
 Well Gly No. 1-25
 Field Little Beaver Creek North
 County Cheyenne State Kansas

Location 1980' FNL & 2055' FEL
 Sec: 25 Twp: 4 S Rge: 37 W

Other Services
 DIL
 MEL

Elevation
 K.B. 3330
 D.F.
 G.L. 3325

Permanent Datum	Ground Level	Elevation	3325
Log Measured From	Kelly Bushing	5	Ft. Above Perm. Datum
Drilling Measured From	Kelly Bushing		
Date	9/12/2011		
Run Number	One		
Type Log	CNL / CDL		
Depth Driller	4770		
Depth Logger	4770		
Bottom Logged Interval	4749		
Top Logged Interval	2950		
Type Fluid In Hole	Chemical		
Salinity, PPM CL	3500		
Density	9.2		
Level	Full		
Max. Rec. Temp. F	126		
Operating Rig Time	4 1/2 Hours		
Equipment -- Location	91 Hays		
Recorded By	D Kerr		
Witnessed By	Clayton Ericson		

Borehole Record		Casing Record					
Run No.	Bit	From	To	Size	Wgt.	From	To
1	12.25	00	297	8.625	24#	00	297
2	7.875	297	4770				

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Thank you for using Log-Tech, Inc.
 (785) 625-3858
 McDonald KS, 7 1/2 South to H RD,
 2 West, 1/2 North, West Into

Database File: c:\warrior\data\credo_gly no. 1-25\credo_091211hd.db
 Dataset Pathname: DIL/credstk
 Presentation Format: cdl
 Dataset Creation: Mon Sep 12 13:29:36 2011
 Charted by: Depth in Feet scaled 1:600

0	Gamma Ray	150
6	Caliper (GAPI)	16

30	Compensated Density		-10
2	Bulk Density		3
15000	Line Tension		0
2.625	DGA	3.425	-0.25
			Correction
			0.25
LSPD			

























